

CIVIL AERONAUTICS AUTHORITY

WASHINGTON, D. C.

INDEX TO

- CAR 04 - CIVIL AIR REGULATIONS, PART 04
- CAAM 04 - CIVIL AERONAUTICS AUTHORITY MANUAL 04
- ANC-5 - STRENGTH OF AIRCRAFT ELEMENTS

OCTOBER 1, 1939

PREFACE

This index covers CAR 04, edition of May 31, 1938 as amended to October 1, 1939, CAAM 04, and ANC-5. (No revisions have as yet been made to the latter two publications.)

The material herein was prepared by Messrs. Norris Fitz Dow and Wilbur H. Gray, in partial fulfilment of the requirements for the Bachelor of Science Degree in Aeronautical Engineering at the Massachusetts Institute of Technology. The authors very kindly gave the Aircraft Airworthiness Section their permission to publish this index for the use and assistance of aeronautical engineers. The Aircraft Airworthiness Section takes this opportunity to thank the authors, on behalf of the Civil Aeronautics Authority, for their cooperation in making this index available for publication.

A-AIR

Abrasions, protection of primary structure from	CAR 04.4014
Absorption of energy	CAAM 04.2411, 04.2420
A.C., aerodynamic center, defined	CAAM 04.1-A1
Accelerations, determination of (drop tests)	CAAM 04.340-B3
Accelerometers, period of	CAAM 04.340-B3
Accessories, engine driven, of multi-engined aircraft powerplant	CAR 04.5891
	CAR 04.65
Accuracy, arithmetical in structural reports	CAAM 04.0326
ACG, airline carriers for goods, equipment for	CAR 04.52
Acid, protection of structure from battery	CAR 04.5821
ACP, airline carriers - passenger, equipment for	CAR 04.53
Aerodynamic center, defined	CAAM 04.1-A1
center, mean, determination of	CAAM 04.217-D
chord, mean, determination of	CAAM 04.217-D
coefficients	CAAM 04.129
Aileron attachment construction to limit flutter	CAR 04.413
control force limits for	CAR 04 Fig. 9
load distribution of	CAR 04 Fig. 7
loading conditions for	CAR 04 Table 5
maneuvering loads	CAR 04.2230
Aileron, statically balanced	CAR 04.424
system, friction in	CAAM 04.43-8
system, differential	CAR 04.233-b
loads on	CAR 04.233
non-differential	CAR 04.233a
Ailerons, balancing of	CAAM 04.424-6a
effect of, on wing analysis, see Condition III _I	
Air density () defined	CAR 04.108
forces, determination of resultant	CAAM 04.217-D
on a biplane	CAAM 04 Fig. 2
table of	CAAM 04 Table II
intakes, for carburetor	CAR 04.662
speed, indicated (V) defined	CAR 04.110
true (V_t) defined	CAR 04.109
standard defined	CAR 04.130
vent for fuel tanks	CAR 04.662
Aircraft, large, balance diagrams for	CAAM 04.0324-4
light	CAAM 04.01
unconventional	CAAM 04.003
Airfoil characteristics, biplane effects on	CAAM 04.129-E
computation of additional	CAAM 04.129-C-Table I
corrected	CAAM 04 Fig. 2
determination of corrected	CAAM 04.129-B
extension of curves	CAAM 04.129-D
force coefficients, illustration	CAAM 04 Figs.8,9,10
Airline carrier, goods	CAR 04.52
passengers, equipment for	CAR 04.53
Airspeed, design, gliding (V_g) defined	CAAM 04.112
indicated (V) defined	CAAM 04.110
level (V_L) defined	CAAM 04.111-1
maneuvering (V_p) defined	CAAM 04.116
indicator calibration	CAR 04.724
heated pitot tube for, installation	CAR 04.530
installation	CAR 04.5800
required for NAC airplane	CAR 04.510

AIR-ANN

limitations	CAR 04.743
maximum in performance test	CAR 04.722
one engine dead	CAAM 04.2220
placard limits	CAAM 04.0612-B6
Airspeeds, determination of - see also speed	CAR 04.211
Airworthiness certificate	CAR 04.00Q 04.04 to 04.042
rating with respect to strength	CAR 04.210
requisites	CAR 04.02
technical data required	CAR 04.03, 04.031
Alclad aluminum alloy sheet, column stresses in	ANC-5 Fig. 5-4
Alloy, see metal or use	
Alloy and metals, miscellaneous	ANC-5 6.0
Altimeter required for NAC airplanes	CAR 04.510
Altimeter, sensitive, for ACP airplanes	CAR 04.532
for NAC airplanes	CAR 04.513
Aluminum alloy beams, see beams	ANC-5 5.2
columns, see columns	ANC-5 5.1
combined loads on	ANC-5 5.4
corrugated sheet, alclad, column stresses in	ANC-5 Fig. 5-4
corrugated sheet, column stresses in	ANC-5 Fig. 5-3
forgings	ANC-5 Table 5-10
joints, fittings, and parts	ANC-5 5.5
properties of (17-8)	ANC-5 Tables 5-2, 5-3, 5-4
properties of (24-8)	ANC-5 Tables 5-5, 5-6
properties of (52-8)	ANC-5 Table 5-7
rivets	ANC-5 Table 5-8
rivets and sheets, shear and bearing strength of	ANC-5 Table 5-11
round tubing, allowable column strength of	ANC-5 Fig. 5-1
sand casting	ANC-5 Table 5-9
streamlined tubing allowable column strength of	ANC-5 Fig. 5-2
torsion in	ANC-5 5.3
tubes, straight line formula for	ANC-5 1.512
tubing, 17 ST., bending modulus of rupture of	ANC-5 Fig. 5-6
tubing, column formulas for	ANC-5 Table 5-1
tubing torsion modulus of rupture of	ANC-5 Fig. 5-7
Amperage in arc welding	CAAM 04.4-12-1d
Amphibians, ACP, equipment for	CAR 04.534
NAC, equipment for	CAR 04.515
wheel position indicators for	CAAM 04.444-1
see seaplanes	
Anchor light for seaplanes ACP	CAR 04.534
for seaplanes NAC	CAR 04.515
installation of	CAR 04.5624
Angle of attack, correction for aspect ratio	CAAM 04.129-B2
high, and torque loads	CAR 04.261
negative high (Condition II)	CAR 04.2132
negative low (Condition IV)	CAR 04.2134
positive high (Condition I)	CAR 04.2131
positive high modified (Condition I _I)	CAR 04.21310
positive low (Condition III)	CAR 04.2133
positive low modified (Condition III _I)	CAR 04.21330
Angles between wires, small	CAAM 04.274
Annealing of bends in copper fuel lines	CAR 04.625

ANT-BAT

Antenna system for ACP airplanes	CAR 04.532
Application for type certificate submitted to branch office	CAAM 04.03
Data required in, see data	CAAM 04.030
Arc length	CAAM 04.4012-1c
welding, see welding	
Area, design wing, computation of	CAAM 04.104
design wing, (S) defined	CAR 04.104
design wing, illustrated	CAAM 04. Fig. 7
gluing, between web and flanges	ANC-5 2.512
solid circular sections	ANC-5 Table 8-2
Aspect ratio corrections	CAAM 04.129-B2
of vertical surfaces	CAR 04.2222b
Assembly drawings	CAAM 04.0320-2d
Atmosphere, standard, defined	CAR 04.130
Automatic pilot, special ruling	CAR 04.2224
Auxiliary devices	CAAM 04.217-B3
tank, pumping fuel to	CAR 04.620
Axial loads in beams	CAR 04.3110
Baffles for fuel tanks	CAR 04.622
Baggage compartments, loads on	CAR 04.265
placards for	CAR 04.466
proof of	CAR 04.361
Balance and weight report for TC	CAR 04.0531
control surface	CAAM 04.0531
diagram for TC	CAAM 04.424
diagram, see Fig. 7, CAAM	CAR 04.0324
report for TC	CAAM 04.0324
report, preliminary	CAR 04.0323
requirements	CAAM 04.0323
tail surface	CAR 04.704
Balancing computations	CAAM 04.427
loads	CAAM 04.218-B4, Table III
loads on horizontal surfaces	CAAM 04.218
loads on horizontal tail	CAAM 04.2210
tail surface, static about hinge lines, ailerons	CAR 04.2210
the airplane, see CAAM Fig. 22	CAR 04.424
Ball and socket joints	CAAM 04.218-B
Ballast and loading schedule	CAAM 04.432-2
location of	CAR 04.72102
size of aircraft permitting	CAR 04.72101b
used, in performance tests	CAR 04.72100a
Barometric pressure compensation for altimeters	CAR 04.7210
Battery, installation of	CAR 04.532
storage, for ATC airplanes instrument day	CAR 04.5321
visual flying day	CAR 04.532
visual flying night	CAR 04.530
for NAC airplanes instrument day	CAR 04.531
instrument night	CAR 04.513
visual night flying	CAR 04.514
	CAR 04.512

BEA-BEN

Beam joints, wing	CAAM 04.4110
Beams, aluminum alloy	ANC-5 5.2
built up	ANC-5 5.22
general	ANC-5 5.20
round tubes	ANC-5 5.210
simple	ANC-5 5.21
thin-walled cylinders	ANC-5 5.211
thin-web	ANC-5 5.23
unconventional	ANC-5 5.212
box, with bending	CAR 04.3116
lateral buckling of	CAR 04.3111
metal spars, general	CAAM 04.311-B
proof of strength of	CAR 04.311
secondary bending of	CAR 04.3110
steel, built up	ANC-5 4.22
general	ANC-5 4.20
round tube	ANC-5 4.210
simple	ANC-5 4.21
thin-walled cylinders	ANC-5 4.211
thin web	ANC-5 4.23
unconventional	ANC-5 4.212
stressed-skin wings	CAAM 04.311-E
thin web metal spars	CAAM 04.311-D
truss type metal spars	CAAM 04.311-C
wing, joints in	CAR 04.4110
torsion in	CAR 04.411
wood, box	ANC-5 2.22
allowable stresses for plywood webs	ANC-5 2.220
shear moduli for plywood webs	ANC-5 2.221
in plywood covered wings	ANC-5 2.23
in pure bending	ANC-5 2.20
joint slippage in	CAR 04.3114
spars	CAAM 04.311-A
spruce, allowable stresses for	ANC-5 Fig. 2-2
torsional instability	ANC-5 2.21
Bearing at an angle to grain	ANC-5 2.501
failure of material in	ANC-5 1.413
in woods other than spruce	ANC-5 2.502
perpendicular and parallel to grain	ANC-5 2.500
strength of aluminum alloy rivets and sheets	ANC-5 Table 5-11
strength of bolts in wood	ANC-5 Fig. 2-3
strength of steel sheets on rivets	ANC-5 Table 4-9
stresses in steel joints	ANC-5 4.501
Bearings, ball and roller, factor of safety	CAR 04.277
for hinges on torque tubes	CAR 04.422
in control system	CAAM 04.277
Belts, safety, in equipment lists	CAAM 04.0322-3e, 04.0322-2b
Bend radii to be given on drawings	CAAM 04.0320-2b
Bending and compression in wood	ANC-5 2.41
and tension in wood	ANC-5 2.42

BEN-BUC

Bending, buckling of flat panels under circular thin-walled cylinders in circular thin-walled truncated cones in elliptic thin-walled cylinders in failure of material in instability failures	ANC-5 Fig. 1-5 ANC-5 1.631 ANC-5 1.652 ANC-5 1.641 ANC-5 1.414 ANC-5 1.422
modulus of rupture of 16ST round tubing secondary, wing spars	ANC-5 Fig. 5-6 CAAM 04.3110
Biplane effects, on airfoil characteristics resultant forces on	CAAM 04.129-E CAAM 04.217-E
Biplanes, internally braced, struts for with single lift truss	CAR 04.414 CAAM 04.2136-2
Birch, bearing strength of	ANC-5 2.502
Block compressive stress, defined	ANC-5 1.341
Boat seaplane landings, bottom loading on steps	CAR 04.256 CAR 04.254
two-wave seaplanes, buoyancy of	CAR 04.255 CAR 04.451
Bolt holes	CAR 04.3115
Bolted joints, bearing in aluminum alloys	ANC-5 5.501 ANC-5 5.50
in wood	ANC-5 2.50
shear	ANC-5 5.500 CAR 04.371
Bolts, allowable bearing load on dimensions to be given on drawings drilled, with elastic stop nuts hollow	CAAM 04.0320-2a CAAM 04.402-2c ANC-5 2.508
in control system	CAR 04.432
in wood, bearing strength of joints with, in steel	ANC-5 Fig. 2-3 ANC-5 4.50
allowable bearing stresses	ANC-5 4.501
allowable shear stresses	ANC-5 4.501
locking of, required	CAAM 04.432-1
pins and screws	CAAM 04.402-2
quality of	CAR 04.4020
spacing of in spar fittings	CAAM 04.402-2
spacing of, in wood, longitudinal	ANC-5 2.504
transverse	ANC-5 2.505
steel, shearing strength, area, and moment of inertia of	ANC-5 Table 4-8
Boots, wing, deflation of (deicers)	CAR 04.5814
Box beams, with bending loads	CAR 04.3116
Bracing, external	CAR 04.410
external in monoplanes	CAR 04.4100
internal, biplanes	CAR 04.414
of control surfaces, external wire	CAAM 04.42-3
wire, redundant	CAAM 04.31-D2 ANC-5 4.52
Brazed joints	CAR 04.4013
Brazing in primary structure	ANC-5 3.00-(17)
Brinell number, defined	ANC-5 1.513
Buckling in columns	CAR 04.3111
lateral	CAAM 04.3111
lateral, of spars	ANC-5 2.12
lateral of wood columns	

BUC-CAB

Buckling of flat rectangular panels critical stress factors for interaction curves for stresses in curved panels stresses in flat panels under combined loadings, flat panels	ANC-5 Fig. 1-5 ANC-5 Fig. 1-5 ANC-5 Fig. 1-6 ANC-5 1.62 ANC-5 1.610 ANC-5 1.611
Bulkheads in boat seaplanes	CAR 04.451, CAAM 04.451-1 CAAM 04.36-C1c CAR 04.436 CAAM 04.444-3
to transmit torque	
Bungee device	
in retracting mechanism	
Buoyancy, boat seaplanes	CAR 04.451, CAAM 04.451
main seaplane floats	CAR 04.450, CAAM 04.450
Bushings in wood joints	ANC-5 2.507
Butt joints in wood	ANC-5 2.511
"C" classification	CAAM 04.031-2
C, subscript, defined	CAAM 04.129-A2
C _B , computation of	CAAM 04.424-3
C _C , correction of, for flaps	CAAM 04.31-B2a
determination of, Eq. 8, XI-C, see table I CAAM &	CAAM 04.129-C1b
extension of	CAAM 04.129-D1f
formula for	CAAM 04.1-C8
value of, for Condition V	CAAM 04.2135-1
C _D , correction for aspect ratio	CAAM 04.129-B2
extension of curves	CAAM 04.129-D1d
C _{D1} , determination of	CAAM 04.129-D1b
C _{Dc} , determination of	CAAM 04.129-D1c
C _L , biplane effects on	CAAM 04.129-E1a
extension of curve	CAAM 04.129-D1
range of values in Condition I	CAAM 04.2131-2
C _M , local value of	CAAM 04.31-A3c
C _{M_a} , determination of	CAAM 04.129-C1c, 04.129- C1d
determination of for Condition I	CAAM 04.2131-3
extension of	CAAM 04.129-D1e
increment to, for condition III	CAAM 04.2133-2
value of for Condition III _I	CAAM 04.21330
C _{M_x} , formula for	CAAM 04.1-C9
C _N , biplane effects on	CAAM 04.129-E1b
determination of, Eq. 7, see Table 1, CAAM, and	CAAM 04.1-C, 04.129-C1a
extension of	CAAM 04.129-D1f
formula for	CAAM 04.1-C7
local value of	CAAM 04.31-A3b
span distribution of, illustration	CAAM 04. Fig. 16, 17
when assumed to vary along span	CAAM 04.217-A5
C _R , formula for	CAAM 04.1-C6
C _{TR} , determination of	CAAM 04.41-1
Cabane bracing with unsymmetrical flight loads	CAAM 04.2150-2
structure, in turn-over	CAR 04.247
Cabins, design	CAR 04.46
doors in	CAR 04.461
emergency doors in	CAR 04.462
lights for ACP airplane	CAR 04.531
Cable in lift trusses	CAR 04.4101, 04.4120

CAB-CHA

Cables at sharp bends, inspection of	CAAM 04.4015-1
control	CAAM 04.43-5
steel	ANC-5 4.53
steel, strength of	ANC-5 Table 4-11
Calibration of airspeed indicator	CAR 04.724
Canadian requirements for seaplane floats	CAAM 04.450-1, 04.452-1
Capacity of cooling system	CAR 04.640
fuel system	CAR 04.620
oil system	CAR 04.630
Carburetor, air intakes for installation of	CAR 04.632
de-icers	CAR 04.6291, 04.532i
heaters, in equipment list	CAAM 04.0322-3f
Cast metals, ultimate compressive stress	ANC-5 1.341
Casting alloys, properties	ANC-5 Table 6-2, 6-3
Castings	CAAM 04.4023
additional ultimate safety factor of	CAAM 04.272
in primary structure	CAR 04.4023
in primary structure, factor of safety of	CAR 04.272
sand, aluminum alloy, properties	ANC-5 Table 5-9
Ceiling, emergency	CAR 04.723
in AC flight tests	CAR 04.733
Center, aerodynamic, defined	CAAM 04.1-A1
of gravity, defined	CAAM 04.1-B
forward	CAAM 04.0531-3c(1)
forward in tab controlled glide	CAR 04.4261
limitations	CAR 04.742
position, variable, effect on balance	CAAM 04.218-B4a
range to be noted on balance report	CAAM 04.03243, CAR 04.0323
rearward	CAAM 04.0531-3c(2)
Center of pressure, extension of	CAAM 04.129-D1g
position, Condition V	CAAM 04.2135-2
position, conversion to moment coefficient (Eq.9)	CAAM 04.129-A3, 04.1-C
Certificate, airworthiness	CAR 04.000
procedure when wanted	CAR 04.04
production (see Part .01)	CAR 04.002
type	CAR 04.001
affidavit of conformity	CAR 04.0530
changes affecting	CAR 04.061
data required	CAR 04.0320
inspection authorization	CAR 04.052
inspection procedure	CAR 04.053
procedure for	CAR 04.05
C.G. see center of gravity	
Chains, spring type connecting links for	CAAM 04.43-6
Chairs, fastening of passenger	CAR 04.464, 04.5890
Changes affecting type certificate	CAR 04.061
by other than holder of TC	CAR 04.0613,
	CAAM 04.0613
drawing	CAR 04.0610
major	CAR 04.0612,
	CAAM 04.0612
minor	CAR 04.0611,
	CAAM 04.0611

CHA-COL

Changes, of primary structure	CAAM 04.041
repair, or alteration of certificated airplanes	CAR 04.060
structural	CAR 04.0533(d)
to be allowed for in drop tests	CAAM 04.340-A2
Checking of data	CAAM 04.0326
Chemical composition	ANC-5 3.00-(21)
Chord distribution of loads	CAAM 04.217-B
line, basic	CAAM 04.218-B2
load distribution, horizontal surfaces	CAAM 04.2211-3
vertical surfaces	CAAM 04.222-1b, 04.222-1c
load, net	CAAM 04.31-B1
running, determination of	CAAM 04.31-B
loadings in stressed skin wings	CAAM 04.217-B1
members, loads in, for truss type metal spars	CAAM 04.311-C3
of truss type metal spars, design of	CAAM 04.311-C4
Chrome-molybdenum round tubing, allowable column	
bending modulus of rupture for	stresses for ANC-5 Fig. 4-2
strength of	ANC-5 Fig. 4-10
	ANC-5 Figs. 4-5, 4-6,
	4-7, 4-8, 4-9
streamlined tubing, allowable column stresses for	ANC-5. Fig. 4-5
Circular sections, areas and moments of inertia of	
solid	ANC-5 Table 8-2
thin-walled cylinders, see cylinders	ANC-5 1.63
Clamps to attach jury struts	CAR 04.4102
Classification of airplanes	CAR 04.C1
Clearance of propellers	CAR 04.611
Clearances of control surfaces	CAAM 04.42-2
Clevis pins as hinge pins	CAR 04.4220
in control system	CAR 04.432
Climb, performance characteristics in	CAR 04.731
requirements	CAR 04.702
landplanes	CAR 04.7020
seaplanes	CAR 04.7021
Clock for ACP airplanes	CAR 04.532
for NAC airplanes	CAR 04.513
Cluster, welded, strength of	ANC-5 4.512
Coefficient, end fixity for Euler formula	ANC-5 1.511
moment, mean effective with flaps	CAAM 04.217D-3i, 04.217D-
	3j
of fixity of chord members of metal spars	CAAM 04.311-C4
of webs of metal spars	CAAM 04.311-C5
See also coefficient in question, as C_N , or	
"Moment", etc.	
Coefficients, aerodynamic	CAAM 04.129, CAR 04.129
correction of	CAAM 04.129-2
for C_M , C_D , etc. see coefficient desired	
moment	CAAM 04.129-3
Column curves, discussion of	ANC-5 1.52
for chrome-molybdenum alloy steel round tubing	ANC-5, Figs. 4-5, 4-6
	4-7, 4-8, 4-9
for corrugated aluminum alloy sheet	ANC-5, Fig. 5-3
for corrugated aluminum alloy sheet, alclad	ANC-5 Fig. 5-4
for heat treated alloy steel round tubing	ANC-5 Fig. 4-4

Column curves, for primary failures	ANC-5 Fig. 1-3
for round aluminum alloy tubing	ANC-5 Fig. 5-1
for solid spruce struts	ANC-5 Fig. 2-1
for streamlined aluminum alloy tubing	ANC-5 Fig. 5-2
formulas, basic	ANC-5 1.27
for chrome-molybdenum round steel tubes	ANC-5 Fig. 4-2
for chrome-molybdenum streamlined steel tubes	ANC-5 Fig. 4-3
for round aluminum alloy tubing	ANC-5 Table 5-1
for round steel tubes	ANC-5 Table 4-1
for 1025 round steel tubes	ANC-5 Fig. 4-1
non-dimensional	ANC-5 1.28
length, effect of on load at failure	ANC-5 1.341
of chord members of metal spars	CAAM 04.311-C4
of webs of metal spars	CAAM 04.311-C5
stresses, steel	ANC-5 4.11, 4.12
yield stress (F_{oc})	ANC-5 1.513
Columns	ANC-5 1.5
aluminum alloy	ANC-5 5.1
formulas	ANC-5 5.10
local failure	ANC-5 5.101
primary failure	ANC-5 5.100
stress curves	ANC-5 5.11, Figs. 5-1, 5-2, 5-3, 5-4
crushing or crippling stress (F_{oc}), defined	ANC-5 1.531
end fixity coefficients for	CAR 04.360
end fixity of	CAR 04.3001
general	ANC-5 1.510
local instability failure of	ANC-5 1.53
long	ANC-5 1.511
primary instability failure of	ANC-5 1.51
short	ANC-5 1.512
steel	ANC-5 4.1
effects of welding	ANC-5 4.102
formulas	ANC-5 4.10
local failure of	ANC-5 4.101
primary failure of	ANC-5 4.100
unconventional cross section	ANC-5 1.54
wood	ANC-5 2.1
lateral buckling of	ANC-5 2.12
local failure of	ANC-5 2.11
primary failure of	ANC-5 2.10
Combined bending and compression on circular cylinders	ANC-5 1.634
bending and torsion on circular cylinders	ANC-5 1.635
concentric and eccentric loadings in wood	ANC-5 2.503
loading conditions, interaction curves for	ANC-5 Fig. 1-2
loading, fabric under	ANC-5 1.424
loadings in aluminum alloy	ANC-5 5.4
loadings in aluminum alloy, bending and compression	ANC-5 4.40
loadings in aluminum alloy, bending and torsion	ANC-5 5.41
loadings in aluminum alloy, bending and torsion and compression	ANC-5 5.42
loadings on steel tubes	ANC-5 4.4
loadings on steel tubes, bending and compression	ANC-5 4.40
loadings on steel tubes, bending and compression and torsion	ANC-5 4.42

Condition III _I , illustrated	CAAM 04, Fig. 13
positive low angle of attack modified	CAAM 04.21330
see also	CAR 04.21330
Condition III _u , unsymmetrical flight	CAAM 04.2150-3
Condition IV, fuel tanks in wing	CAR 04.2152
illustrated	CAR 04.2134
negative low angle of attack	CAAM 04, Fig. 14
Condition V, illustrated	CAAM 04.2134
inverted flight	CAR 04.2134
Condition V _u	CAAM 04, Fig. 15
Condition VI, gliding	CAAM 04.2135
illustrated	CAR 04.2135
with indeterminate wing cellule	CAR 04.2153
Condition VII, positive gust, flaps deflected	CAR 04.2136
Condition VIII, negative gust, flaps deflected	CAAM 04.2136
Condition IX, dive, flaps deflected	CAAM 04, Fig. 15
Cones, thin-walled, truncated, circular, in bending	CAAM 04.31-D3
in compression	CAR 04.2141
in torsion	CAR 04.2143
in transverse shear and bending	CAR 04.2143
under other combined loadings	ANC-5 1.652
Confidential data	ANC-5 1.641
Conformity, Statement of	ANC-5 1.653
Connecting parts	ANC-5 1.654
Connection of cooling system	ANC-5 1.655
of oil system	CAR 04.055
Constructional methods	CAR 04.0530
Control force limits for aileron	CAAM 04.402
for elevator	CAR 04.642
horns, welding of	CAR 04.634
linkages, inspection of	CAR 04.401
stick between pilot and passenger	CAR 04, Fig. 9
surface chord loadings	CAR 04, Fig. 8
surface hinges and system joints	CAAM 04.42-4
bearing stress in	CAAM 04.4015-1
surface loads	CAR 04.430
unit loadings	CAAM 04.22-4
surface stops, location given on drawings	CAAM 04.277, CAR 04.277
surfaces, detail design of	ANC-5 4.501-(3)
surfaces, installation of	CAAM 04.22, CAR 04.22
surfaces, proof of	CAAM 04.22-3
system, detail design of	CAAM 04.0320-2c
flap controls	CAAM 04.42, CAR 04.42
for flaps and tabs	CAR 04.420
installation of	CAAM 04.32, CAR 04.32
irreversible	CAAM 04.43, CAR 04.43
locks	CAR 04.434,
single cable	CAAM 04.234 [†]
	CAR 04.430
	CAR 04.424
	CAR 04.438
	CAR 04.437

CONT-CP

Control system, joints in	CAR 04.432
loading conditions for	CAR 04: Table 6
loads	CAAM 04.22
aileron	CAR 04.233
flap and tab	CAR 04.234
rudder	CAR 04.232
wires	CAR 04.231
locks	CAR 04.438
proof of	CAAM 04.33, CAR 04.33
pulleys, location given on drawings	CAAM 04.0320-2c
rigidity of	CAAM 04.43-11
spring devices in	CAR 04.436
stops in	CAR 04.431
tab controls	CAR 04.435
welds in	CAR 04.433
Controllable pitch mechanism, stops for	CAR 04.610
Controllability requirements	CAR 04.703
Controls, dual, with opposite loads	CAAM 04.43-10
flap	CAAM 04.434, CAR 04.434
ignition	CAR 04.6511
powerplant	CAR 04.651
primary, unit, in plane of prop	CAR 04.4630
propeller pitch	CAR 04.6512
single-cable	CAAM 04.437, CAR 04.437
tab	CAAM 04.435, CAR 04.435
throttle	CAR 04.6510
Cooling system, drains	CAR 04.642
filler openings	CAR 04.644
piping	CAR 04.641
radiators	CAR 04.64
Copper fuel lines, bends in	CAR 04.625
Correction factors, for aluminum alloy round tubes and circular corrugations	ANC-5 Fig. 1-4
Corrosion in primary structure	CAR 04.4014
resistant steel, properties of	ANC-5 Table 4-6
Corrugated aluminum alloy sheet, column stresses in	ANC-5 Fig. 5-3
aluminum alloy sheet alclad, column stresses in sections	ANC-5 Fig. 5-4
Corrugations, circular, geometrical properties of	ANC-5 1.73
material properties correction factors for	ANC-5 Fig. 5-5
Cotter pins, use of	ANC-5 Fig. 1-4
Covering, attachment of, fabric	CAAM 04.43-6
fabric	CAAM 04.415-2
metal, wing	CAAM 04.415, CAR 04.415
strength of	CAR 04.416
Cowling, engine	CAR 04.314
manifolding, and firewall	CAR 04.663
C.P., extension of	CAR 04.66
of horizontal tail	CAAM 04.129-D1g
position, Condition V	CAAM 04.218-B1c
conversion to moment coefficient	CAAM 04.2135-2
and equation 9	CAAM 04.129-A3
	CAAM 04.1-C

CRE-DEF

Crew and passenger, standard weight of	CAR 04.90
Crippling stress (F_{cc})	ANC-5 1.631
Crop dusting aircraft (R)	CAAM 04.031-5b
Crushing stress (F_{cc})	ANC-5 1.631
stresses of corrugated aluminum alloy sheets	ANC-5 Fig. 5-3
Alolad	ANC-5 Fig. 5-4
Curved panels	ANC-5 1.62
Cut-outs in trailing edge, effect on span distribution	CAAM 04.217-A4
in trailing edge, effect on wing area	CAAM 04.104-2
Cylinders, thin-walled, aluminum alloy	ANC-5 5.211
thin-walled circular in bending	ANC-5 1.631
in combined bending and torsion	ANC-5 1.635
in combined bending and compression	ANC-5 1.634
in compression	ANC-5 1.630
in torsion	ANC-5 1.632
in transverse shear and bending	ANC-5 1.633
elliptical thin-walled	ANC-5 1.64
bending	ANC-5 1.641
compression	ANC-5 1.640
other combined loads	ANC-5 1.644
torsion	ANC-5 1.642
transverse shear and bending	ANC-5 1.643
"d", formula for	CAAM 04.1-C5
"p", subscript, defined	CAAM 04.129-A2
Damping, horizontal surfaces	CAAM 04.2212, CAR 04.2212
vertical surfaces	CAAM 04.2221, CAR 04.2221
Dardelet threaded parts, restrictions to use of	CAAM 04.4020-3
Data authenticated	CAR 04.0542
confidential	CAR 04.055
partial (TC)	CAR 04.0500
required for airworthiness certificate	CAAM 04.031, CAR 04.031
required for large projects	CAAM 04.032
required for service type aircraft	CAAM 04.031-3
required for single airplane	CAAM 04.031-4
required for TC	CAAM 04.032-1
required technical	CAAM 04.03
submitted to a branch office	CAR 04.030
technical, submitted for airworthiness rating	CAR 04.03
Datum for balance diagram	CAAM 04.0324
Definitions	CAR 04.1
and symbols for metals	ANC-5 3.00
including standard symbols, values and formulas	CAAM 04.1
structural	ANC-5 1.3
Deflections, allowance for in design of hinges	CAAM 04.422-1b
axial, formulas for	ANC-5 1.23
bending, formulas for	ANC-5 1.24
of jig, in measuring deformations	CAAM 04.201
torsion, formulas for	ANC-5 1.25
Deformations due to loading conditions	CAAM 04.201
of primary structure	CAR 04.201
transverse, formulas for	ANC-5 1.26

DRAW-ELO

Drawings, substitution of plots for, for TC	CAR 04.0320g
three view	CAAM 04.0320g
for airworthiness certificate	CAR 04.031a
for TC	CAR 04.0320g
Drop, height of, measurement of, in drop test	CAAM 04.340-B5
test, allowance for changes in	CAAM 04.340-A2
allowance for wing lift in	CAAM 04.340-A3
for three point landing	CAR 04.2420
margin between load factor developed and	
design	CAAM 04.240-4b
resulting in yielding	CAAM 04.340-A1
to determine energy absorption for level	
landing	CAR 04.2411
tests of landing gear	CAR 04.340
Dual controls, with opposite loads	CAAM 04.43-10
Dump valves	CAR 04.6270
Dynamic balance coefficient	CAAM 04.424-2
computation	CAAM 04.424-3
of controls	CAAM 04.424
Eccentric and concentric, combined loadings in wood	ANC-5 2.503
Eccentricity pattern of joint in truss type beams	CAAM 04.311-C
Effective width constants for aluminum alloy sheets	ANC-5 Table 1-1
width of sheet for sheet-stiffener combinations	ANC-5 Fig. 1-7
Efficiency of steel cable terminals	ANC-5 4.530
EI, correction factors for computing	CAAM 04.311-B2
equivalent value, determination of	CAAM 04.311-B1
of truss type spars	CAAM 04.311-C2
Elastic instability failures, defined	ANC-5 1.420
stop nuts, restrictions on use	CAAM 04.4020-2
Elasticity modulus of (E), defined	ANC-5 1.331
Electrical equipment, anchor lights	CAR 04.5824
battery	CAR 04.5821
fuses	CAR 04.5822
generator	CAR 04.5823
running load of	CAR 04.58230
installation	CAR 04.582
instrument lights	CAR 04.5826
landing lights	CAR 04.5825
master switch	CAR 04.5828
position lights	CAR 04.5827
Electrode type and material for arc welding	CAAM 04.4012-1c, 04.4012-1d
Elevator control force	CAR 04.2210
control system, loads on	CAR 04.231
loads, balancing	CAR 04.2210
effect of tab on	CAR 04.2213
maneuvering	CAR 04.2211
Elevators, balancing of	CAAM 04.424-6c
connected	CAR 04.423
control force limits for	CAR 04. Fig. 04-8
with dihedral	CAAM 04.423-1
Elongation defined	ANC-5 3.00-(5)

	END-EQU
End fixity coefficient in Euler formula	ANC-5 1.511
coefficients	CAR 04.360
margin for bolts in spruce	ANC-5 Fig. 2-4
Energy absorption	CAAM 04.2411
in level landing	CAR 04.2411
in three point landing	CAR 04.2420
tests	CAAM 04.340, CAR 04.340
Engine driven accessories, on aircraft	CAR 04.652
on multi-motored aircraft	CAR 04.5891
installation	CAR 04.6
limitations	CAR 04.744
mount, design conditions for	CAR 04.260, 04.261,
	04.2610, 04.262
proof of	CAAM 04.36
side loads on	CAR 04.262
under gust load	CAAM 04.2160
up load on	CAR 04.263
mounts, end fixity coefficients of	CAR 04.360
proof of	CAR 04.36
of type other than covered by TC installation of	CAAM 04.0612B
placard limits	CAAM 04.0612-B7
provision for increased power	CAAM 04.0612-P9
requirements, miscellaneous	CAR 04.89
torque loads and high angle of attack	CAR 04.260, 04.261
Engines certificated as airworthy	CAR 04.80
connection of fuel lines to	CAR 04.625
controls	CAR 04.651
cowling	CAR 04.663
firewall	CAR 04.664
ignition switches	CAR 04.6511
instruments	CAR 04.350
throttle controls	CAR 04.6510
Equipment design satisfactory to Authority	CAR 04.500
electrical, installation of	CAR 04.582
fire extinguisher	CAR 04.502
for ACG	CAR 04.52
for ACP	CAR 04.53
for air carrier landplanes, instrument day	CAR 04.532
for air carrier landplanes, instrument night	CAR 04.533
for air carrier landplanes, visual contact day	CAR 04.530
for air carrier landplanes, visual contact night	CAR 04.531
for NAC	CAR 04.51
landplanes, instrument day	CAR 04.513
instrument night	CAR 04.514
visual contact day limited	CAR 04.510
visual contact day unlimited	CAR 04.511
visual contact night	CAR 04.512
seaplanes and amphibians	CAR 04.515, 04.534
general	CAR 04.5
installation	CAR 04.58
instruments	CAR 04.580
miscellaneous	CAR 04.589
of airspeed indicator	CAR 04.5800
of fuel quantity gauge	CAR 04.5802, 04.628
of gyroscopic instruments	CAR 04.5805

EQU-FAI

Equipment installation of magnetic compass	CAR 04.5803
of navigation instruments	CAR 04.5804
of radio	CAR 04.583
life preserver	CAR 04.501
lists of for TC	CAR 04.0322
sample	CAAM 04.0322
to be omitted from three view drawings	CAAM 04.0320(g)
radio	CAR 04.503
required, Class I	CAAM 04.0531-3a
Class II	CAAM 04.0531
Class III	CAAM 04.0531-3c
safety, installations of	CAR 04.581
Equivalent drag area (Sp)	CAAM 04.1-A3
Euler formula, ANC-5 Equation 1.22	ANC-5 1.27
discussion of	ANC-5 1.511
modified for short columns	ANC-5 1.512
Examination discontinuance of for airworthiness	
certificate	CAR 04.0401
discontinuance of for TC	CAR 04.0435
Exhaust manifolds, construction and installation	CAR 04.661
Exits, emergency	CAR 04.452
Extinguisher, fire, approved	CAR 04.502
fire, installation	CAR 04.5811
Extruded sections, grain in	CAAM 04.402-3
Eyebolts, fillets for	CAR 04.4022
F _p , formula for	CAAM 04.1-C11
F _{pr} , formula for	CAAM 04.1-C15
F _x , formula for	CAAM 04.1-C10
Fabric covering	CAAM 04.415, CAR 04.415
method of attaching	CAAM 04.415-2
Fabrication methods	CAR 04.401
Factor, load	CAR 04.212
maneuvering load	CAR 04.2120, Fig. 3
of safety, minimum	CAR 04.2122
yield	CAR 04.201
of utilization, computation of	ANC-5 1.424(5)
Factors of Safety	CAR 04.27
for ball or roller bearings	CAR 04.277
for castings	CAR 04.272, Table 7
for control surface hinges	CAR 04.277
for double drag trusses	CAR 04.274
for fittings	CAR 04.271, Table 7
for parallel double wires	CAR 04.273, Table 7
for torque tubes used as hinges	CAR 04.276, Table 7
for wires at small angles	CAR 04. Table 7
multiplying	CAR 04.27
Fairleads to prevent chafing	CAAM 04.43-7
Failure defined	ANC-5 1.40
instability	ANC-5 1.42
discussion of	ANC-5 1.420
under bending	ANC-5 1.422
under combined loads	ANC-5 1.424
under compressive loads	ANC-5 1.421
under torsion loads	ANC-5 1.423

FAIL-FLA

Failure, how caused	ANC-5 1.410
bearing	ANC-5 1.413
bending	ANC-5 1.414
direct tension or compression	ANC-5 1.411
due to stress concentration and fatigue	ANC-5 1.416
from combined stresses	ANC-5 1.415
local, of unconventional columns	ANC-5 1.541
of columns, local instability	ANC-5 1.53
primary instability	ANC-5 1.51
of material	ANC-5 1.41
shear	ANC-5 1.412
types of	ANC-5 1.4
Fatigue failure	ANC-5 1.416
Feed in fuel system	CAR 04.620
Filler openings, cooling system	CAR 04.644
fuel systems	CAR 04.6290
oil systems	CAR 04.644
Fin area, defined	CAAM 04.222-1a
damping	CAR 04.2221
loads, maneuvering	CAR 04.2220
Fire, design of manifold, cowling, firewalls, for	
prevention of	CAR 04.660
extinguisher, approved	CAR 04.502
for ASP airplanes	CAR 04.530
for MAC airplanes	CAR 04.510
installation of	CAR 04.5811
Firewall, distance of fuel tank from	CAR 04.621
location of	CAR 04.6640
manifolding and cowling, construction of	CAR 04.66, 04.664
First-aid kit required for MAC airplanes	CAR 04.510
Fittings, aluminum alloy, see joints	ANC-5 5.5
and parts, proof of	CAAM 04.37
at end of wood spars	CAAM 04.402-2
defined to include bearing	CAAM 04.271
definitions of	CAR 04.271
drawings of	CAAM 04.402-4
end, installation of	CAAM 04.400-3
factor of safety of	CAR 04.271
in fuel line	CAR 04.625
load factor for, in control system	CAAM 04.230-4
main, inspection of	CAAM 04.4015-1
progressive failure of	CAR 04.402
proof of, in primary structure	CAR 04.37
steel	ANC-5 4.5
wire anchorages	CAR 04.4031
wood	ANC-5 2.5
Fixity coefficient, end	CAR 04.360
end, for Euler formula	ANC-5 1.511
of chord members of metal spars	CAAM 04.311-C4
of webs of metal spars	CAAM 04.311-C5
Flange and web area for gluing	ANC-5 2.512

FLAP-FLU

Flap attachments	CAR 04.413
control system, loads on	CAR 04.234
controls, and operating mechanism	CAR 04.434
installation to prevent flutter	CAR 04.425
Flaps, control system for	CAAM 04.234
controls for	CAAM 04.434
deflected, effect on spar loading	CAAM 04.31-A3d
design condition for, see Conditions VII, VIII, IX	
effect on Conditions VII and VIII	CAAM 04.2140-1
inboard of aileron, or full span	CAAM 04.2140-2
local loading on wing	CAAM 04.2140-3
partial span, effect on C_D	CAAM 04.31-B2a
trailing edge, internally braced monoplane wings	CAAM 04.2140
wing	CAAM 04.425
loads on	CAAM 04.224, CAR 04.224
Flare and landing (AC)	CAR 04.730
Flares, landing, for ACP airplanes	CAR 04.531
for NAC airplanes	CAR 04.512
installation of	CAR 04.5813
Flat panels	ANC-5 1.61
buckling of	ANC-5 1.610, 1.611
ultimate strength of	ANC-5 1.61
Flight conditions, see Condition	
inverted, Condition V	CAR 04.2135
load tests	CAR 04.303
mechanic, instruments for	CAR 04.650
testing for performance	CAR 04.720
test report	CAAM 04.0532
Float bottoms, curved	CAAM 04.45-1
bracing, analysis of	CAAM 04.34-2
loads on	CAR 04.257
loads on bottom of	CAR 04.2570
seaplane landings with side load	CAR 04.253
with vertical reactions	CAR 04.252
wing tip, effect on primary structure	CAR 04.2580
wing-tip, loads on	CAR 04.258
Floats and hulls	CAAM 04.45
design of	CAR 04.453
effect of drag of, in producing local loads	CAAM 04.31-B3
general	CAR 04.45
main seaplane, buoyancy of	CAR 04.450
water-tight compartments	CAR 04.4500
proof of	CAR 04.35
water stability with auxiliary	CAR 04.452
Flotation device, approved	CAR 04.501
Flutter and vibration	CAR 04.707
balancing of ailerons to prevent dynamic	CAR 04.4240
static	CAR 04.424
due to aileron and flap attachment	CAR 04.413
installation of flap to prevent	CAR 04.425

FLUT-FUS

Flutter prevention	CAAM 04.404
prevention measures, see CAR 04.404 for references with new engine	CAAM 04.0612-B1
Flying boat, see boat	
Forces, basic, in flight conditions	CAAM 04. Fig. 22
resultant air, determination of	CAAM 04.127-D
resultant air, determination of, on biplanes	CAAM 04.217-E, Fig. 21
Forgings, aluminum alloy, properties of	ANC-5 Table 5-10
Form factors, in shear tests	ANC-5 1.350
Formulas and standard values	CAAM 04.1-C
basic column	ANC-5 1.27
combined stresses	ANC-5 1.22
commonly used structural	ANC-5 1.2
deflections, axial	ANC-5 1.28
deflections, bending	ANC-5 1.24
deflections, torsion	ANC-5 1.25
non-dimensional	ANC-5 1.28
simple unit stresses	ANC-5 1.21
transverse deformations	ANC-5 1.26
Frequency, dispersion of	CAAM 04.323-8
natural, determination of	CAAM 04.323-3
Fuel capacity and feed	CAR 04.620
plate showing	CAR 04.4631
carried in performance tests	CAR 04.711
drains	CAR 04.628
filler openings	CAR 04.6290
gage	CAR 04.624
lines and fittings	CAR 04.625
pumps	CAR 04.620
strainers	CAR 04.626
system, check of	CAR 04.725
requirements, miscellaneous	CAR 04.629
systems	CAR 04.62
tank construction	CAR 04.622
installation	CAR 04.621
strength	CAR 04.623
tanks, optional, in equipment lists	CAAM 04.0322-3b
utility	CAR 04.624
valves	CAR 04.627
Fumes in passenger compartment	CAR 04.467
near fuel tanks	CAR 04.621
Fuselage, balancing loads on, symmetrical	CAAM 04.36-B2
unsymmetrical	CAAM 04.36-B3
design details of	CAR 04.46
doors in	CAR 04.461
with relation to propeller	CAR 04.4610
side of fuselage specified	CAR 04.4611
drag area, variation of, with gross weight	CAAM 04. Fig. 6
exits, emergency	CAR 04.462
forward portion of, design conditions for	CAR 04.260
forward portion of, under gust load	CAAM 04.2160
proof of	CAAM 04.36, CAR 04.36
provision for turn-over	CAR 04.460
special analysis methods of	CAAM 04.36-C
stressed-skin, analysis of	CAAM 04.36-D

FUS-HOR

Fuses, installation	CAR 04.5822
spare, for ACP airplanes	CAR 04.530
for NAC airplanes, instrument day flying	CAR 04.513
for NAC airplanes, visual night flying	CAR 04.513
Gasoline, standard weight of	CAR 04.90
Gage, fuel	CAR 04.624
oil	CAR 04.633
Generator for ACP airplanes	CAR 04.531
for NAC airplanes	CAR 04.513
installation	CAR 04.5823
Gliding, Condition VI	CAR 04.2136
speed factor	CAR 04. Fig. 1
Glue joints	ANC-5 2.51
area between web and flange	ANC-5 2.512
discussion	ANC-5 2.510
scarf	ANC-5 2.511
use of	CAR 04.4010
Gluing	CAAM 04.4010
Grommets for drag wire inspection	CAAM 04.4015-1
Ground and water characteristics	CAR 04.708
clearance of propellers	CAR 04.611
loads	CAR 04.24
Gust at reduced weight	CAAM 04.2160, CAR 04.2160
design velocity (V) defined	CAR 04.117
load factors	CAR 04.2121
negative, flaps deflected see Condition VII	
positive, flaps deflected see Condition VIII	
Gusts on vertical surfaces	CAAM 04.2222
Gyroscopic instruments for ACP	CAR 04.532
instruments, installation	CAR 04.5805
rate of turn indicator for NAC airplanes	CAR 04.513
Handbook, purpose and use of	ANC-5 1.0
Hardness, versus tensile strength of S.A.E. steels	ANC-5 Table 4-7
Hardwood laminations, effect of on wood joints	ANC-5 2.506
Heating systems	CAR 04.665
Heat treatment, allowance for shrinkage from	CAAM 04.400-3
High-lift device, effect on chord loads	CAAM 04.217-B3
Hinges	CAAM 04.422
clevis pins as	CAR 04.4220
control surface and control system joints	CAR 04.277
in control surfaces, bearing stresses in	ANC-5 4.501-(3)
of control surfaces	CAAM 04.277
of strap type	CAR 04.422
torque tube used as	CAR 04.276
Holes, bolt	CAR 04.3116
for drawings	CAAM 04.4014
Horizontal surfaces, see surfaces	
tail balancing loads	CAR 04.2210
damping loads	CAR 04.2212
maneuvering loads	CAR 04.2211
tab effects	CAR 04.2213

	HOS-INV
Hose connections in fuel lines	CAR 04.625
Hulls	CAR 04.45
and floats	CAAM 04.45
buoyancy of	CAR 04.451
proof of	CAR 04.35
water stability of	CAR 04.452
Hydro-stabilizers	CAR 04.2590
Ice, arrangements of fuel tank airvents to prevent	CAR 04.622
eliminators	CAR 04.5814
formation in carburetors	CAR 04.6291
surface reinforced for, near propeller	CAR 04.466
Icing conditions, indication of	CAR 04.532
Identification plate	CAR 04.532
Ignition switches	CAR 04.6511
IN-line drop tests	CAAM 04.340-C
Inspection	CAAM 04.4015
discontinuance of forTC	CAR 04.0535
ground	CAR 04.0533
openings	CAR 04.4015
structural	CAR 04.051
type, authorization of	CAR 04.052
procedure	CAR 04.053
Instability failures	ANC-5 1.42
discussion of	ANC-5 1.420
local, of columns	ANC-5 1.53
primary of columns	ANC-5 1.51
under compressive loadings	ANC-5 1.421
Installation, cooling systems	CAR 04.64
engines	CAR 04.60
fuel systems	CAR 04.62
instruments, controls, accessories	CAR 04.65
lubrication systems	CAR 04.63
manifolding, cowling, firewall	CAR 04.66
miscellaneous	CAR 04.69
powerplant	CAR 04.6
propellers	CAR 04.61
requirements	CAR 04.58
electrical	CAR 04.582
instruments	CAR 04.5800
miscellaneous	CAR 04.589
radio	CAR 04.583
safety equipment	CAR 04.581
Instrument installation requirements	CAR 04.580
gyroscopic instruments	CAR 04.5805
magnetic compass	CAR 04.5803
navigation instruments	CAR 04.4636, 04.5804
of airspeed indicator	CAR 04.5800
powerplant instruments and controls	CAR 04.5801
lights, installation of	CAR 04.5826
navigation	CAR 04.4638
powerplant	CAR 04.650
Intakes, air	CAR 04.662
Interference, radio, elimination of	CAR 04.532
Inverted flight, Condition V	CAR 04.2135

	J - LAM
J, defined	CAR 04.121
J_u , defined	CAR 04.122
J_v , defined	CAR 04.123
Jig deflection, in measuring deformations	CAAM 04.201
Johnson formula for round steel tubes, short column	ANC-5 1.512
Joint slippage in wood beams	CAR 04.3114
Joints	CAAM 04.404
aluminum alloy-	ANC-5 5.5
bolted and riveted	ANC-5 5.50
in bearing	ANC-5 5.501
in shear	ANC-5 5.500
tension lugs	ANC-5 5.52
welded	ANC-5 5.51
in control system	CAAM 04.277, 04.432, CAR 04.432
in primary structure, proof of	CAR 04.37
in wing beams	CAAM 04.4110, CAR 04.4110
prevention of loosening of	CAR 04.402
steel	ANC-5 4.5
allowable bearing stresses	ANC-5 4.501
allowable shear stresses	ANC-5 4.500
brazed	ANC-5 4.52
welded	ANC-5 4.51
allowable loads	ANC-5 4.511
clusters	ANC-5 4.512
effect on base metal	ANC-5 4.510
wood	ANC-5 2.5
bolted	ANC-5 2.511
bearing at an angle to grain	ANC-5 2.501
bearing in woods other than spruce	ANC-5 2.502
bearing parallel and perpendicular to grain	ANC-5 2.500
bushings	ANC-5 2.507
combined concentric and eccentric loads	ANC-5 2.503
effects of hardwood laminations	ANC-5 2.506
hollow bolts	ANC-5 2.508
longitudinal bolt spacing	ANC-5 2.504
transverse bolt spacing	ANC-5 2.505
butt	ANC-5 2.511
glued	ANC-5 2.51
discussion	ANC-5 2.511
scarf	ANC-5 2.511
Jury struts	CAR 04.4102
effect of in computing strength of lift struts	CAAM 04.21-D1
K_g , specified	CAR 04.211, Fig. 1
K_p , specified	CAR 04.211, Fig. 2
Keys, Woodruff, in tubing	CAAM 04.432-3
L, subscript, defined	CAAM 04.129-A2
Lacing of fabric and rib spacing	CAAM 04.415-2
Laminations of hardwood, effect of	ANC-5 2.506

LAN-LAND

Landing and flares	CAR 04.730
braked	CAR 04.245
controllability in	CAR 04.703
gear, deficiency in strength of (R)	CAAM 04.031-6b
detail design of	CAAM 04.44, CAR 04.44
drop tests of	CAR 04.340
loads on wing structure	CAR 04.417
main, tests of, 1st method	CAAM 04.340-B
2nd method	CAAM 04.340-C
nose wheel type, tests of	CAAM 04.340-E
position indicator	CAR 04.444
for NAC airplanes	CAR 04.510
manual operation	CAR 04.4441
proof of	CAR 04.34
retractable, control devices, drawings of	CAAM 04.0320-2e
retracting mechanism	CAR 04.444
lock	CAR 04.4440
shock absorber deflection	CAR 04.241
shock absorption, landing	CAR 04.440
taxing	CAR 04.441
tests at provisional weight	CAAM 04.340-F
unconventional	CAAM 04.44-2
ground loads	CAAM 04.240
level, see CAR 04. Fig. 10	CAR 04.241
test	CAAM 04.340-B2
lights, for ACP airplanes	CAR 04.531
installation of	CAR 04.5825
required for NAC airplanes	CAR 04.512
loads, general	CAAM 04.240
on float seaplanes	CAAM 04.250-2
on flying boats	CAAM 04.250-3
on large flying boats	CAAM 04.250-4
side, on flying boats	CAAM 04.250-5
on tail wheel or skid	CAAM 04.246
one wheel	CAR 04.244
on water	CAAM 04.250
special considerations	CAAM 04.240-4
speed requirements	CAR 04.700
not met	CAAM 04.031-6b
step, boat seaplanes	CAR 04.254
three point	CAR 04.242
test	CAAM 04.340-B2
turn-over	CAR 04.245
two-wave, boat seaplanes	CAR 04.255
wheels	CAR 04.442
with inclined reactions, float seaplanes	CAR 04.251
with nose wheel type gear	CAAM 04.240-2
with one wheel	CAAM 04.244
with side load, float seaplanes	CAR 04.253
with side loads	CAR 04.243
with skis	CAAM 04.240-3
with tail wheel type gear	CAAM 04.240-1, Fig. 24
with vertical reactions, float seaplanes	CAR 04.252

LAND-LOA

Landplanes, ACP, equipment for instrument day flying	CAR 04.532
equipment for instrument night flying	CAR 04.533
equipment for visual contact night flying	CAR 04.531
conversion of, to skiplanes	CAAM 04.0612-C
NAC, equipment for	CAR 04.510
instrument day flying	CAR 04.513
instrument night flying	CAR 04.514
night flying	CAR 04.512
unlimited distance	CAR 04.511
Lateral balance requirements	CAR 04.704
buckling	CAR 04.3111
of spars	CAAM 04.3111
Leading edge loads	CAAM 04.217-B2
of rib, test of	CAAM 04.313-A2
edges, sharp, on movable surfaces and flutter	CAAM 04.404-1
Leakage into pilot's compartment	CAR 04.4634
of fuel tanks	CAR 04.623
Level landing test	CAAM 04.340-B2
Leveling means	CAR 04.91
Life preserver	CAR 04.501
Lift bracing, wire	CAR 04.410
strut, crushing by jury strut	CAR 04.4102
truss analysis	CAAM 04.31-D
front, critical condition for see Condition I	
lift wire cut	CAR 04.2161
members transmitting landing loads	CAR 04.279
multiple strand wire in	CAR 04.4101
rear, see Condition V	
rear, when C_{M_a} is small	CAAM 04.21310-1b
single	CAAM 04.2134-3
wire cut	CAR 04.2161
Lights, anchor, for ACP seaplanes	CAR 04.534
for NAC seaplanes	CAR 04.515
installation of	CAR 04.5824
instrument, installation of	CAR 04.5826
landing, installation of	CAR 04.5825
position in equipment list	CAAM 04.0322-3e
installation of	CAR 04.5827
required for ACP airplanes	CAR 04.531
for NAC airplanes	CAR 04.512
Liners, metal, for fuel lines	CAR 04.625
Lines, fuel, construction of	CAR 04.625
Links, spring type connecting	CAAM 04.43-6
Lists, drawing (TC) sample	CAAM 04.0321
equipment (TC) sample	CAAM 04.0322
recommended form see	CAAM 04. Fig. 3
Load, balancing, defined	CAR 04.128
distribution, aileron	CAR 04. Fig. 7
balancing, horizontal tail	CAR 04. Fig. 4
damping, tail	CAR 04. Fig. 8
maneuvering, tail	CAR 04. Fig. 5
of wing	CAR 04.217
drag, on wing cellule	CAAM 04.217-C1
factor, (n) defined	CAR 04.119
"net"	CAAM 04.218-B1b
factors, flight, wing	CAR 04.212

18612

LOA-LOADS

Load factors, gust	CAR 04.2121
increment	CAR 04.21212
landing gear	CAAM 04.240-4
level and three point landing	CAR 04. Fig. 10
maneuvering	CAR 04.2120, Fig. 3
increment Condition L	CAR 04. Fig. 3
net	CAR 04.212
limit, defined	CAR 04.120
local from propeller thrust	CAAM 04.31-B3
ratio, use of, in combined loading	ANC-5 1.424
running and torsion at elastic axis	CAAM 04.31-C
chord	CAAM 04.31-B
electrical	CAR 04.56230
on spars	CAAM 04.31-A2
when spar does not extend to wing tip	CAAM 04.31-A3
side, landing gears	CAAM 04.243
test required	CAR 04.304
tests, for proof of structure	CAR 04.302
on similar structures	CAAM 04.301
structural	CAAM 04.3022
ultimate, defined	CAR 04.124
yield, defined	CAR 04.125
Loading conditions, ailerons	CAR 04. Table 5
control systems	CAR 04. Table 6
horizontal tail	CAR 04. Table 3
in performance tests	CAR 04.721
special	CAR 04.26
structural	CAAM 04.2
vertical tail	CAR 04. Table 4
design power, $(\frac{W}{P})$, defined	CAR 04.106
design wing, $(\frac{W}{S})$, defined	CAR 04.107
Loadings, chord	CAAM 04.217-B
combined	ANC-5 Fig. 1-2
failure under	ANC-5 1.424
in steel	ANC-5 4.4
on wood	ANC-5 2.4
concentric and eccentric in wood	ANC-5 2.503
interaction curves for combined	ANC-5 Fig. 1.2
span	CAAM 04.217-A
special	CAAM 04.217-C
parasite drag	CAAM 04.217-C1
propeller thrust	CAAM 04.217-C2
Loads, air, on struts	CAR 04.267
balancing	CAAM 04.218
control surface	CAAM 04.22, CAR 04.22
control system	CAAM 04.230
flight	CAR 04.21
from baggage	CAR 04.265
from safety belts	CAR 04.2650
ground	CAR 04.24
horizontal tail	CAR 04.221
high angle of attack and torque	CAR 04.261
landing, on wing structure	CAR 04.417
limit on tab	CAR 04.225

LOADS-MAC

Loads, local	CAR 04.265
on aileron system	CAR 04.233
on control system	CAR 04.23, 04.265
on elevator system	CAR 04.231
on flap system	CAR 04.234
on rudder system	CAR 04.232
on seaplane float bottoms	CAR 04.2570
on seaplane floats	CAR 04.257
on seawings, spars	CAR 04.2590
on wing spars	CAAM 04.31-A
when they do not extend to wing tip	CAAM 04.31-A5
on wing tip floats	CAR 04.258
panel point, computation of	CAAM 04.36-B1
passenger	CAR 04.264
rigging	CAR 04.266
side in landing	CAR 04.243
side, on engine mount	CAR 04.262
torque	CAR 04.260
up, on engine mount	CAR 04.263
vertical tail	CAR 04.222
water, ability of structure to distribute	CAR 04.35
water, general	CAR 04.25
miscellaneous	CAR 04.259
Local crushing or crippling stress (F_{cc})	ANC-5 1.531
instability failure of columns	ANC-5 1.53
Look for control system	CAR 04.438
for landing gear retracting mechanism	CAR 04.4440
for pilot's compartment door	CAR 04.4637
safety for all tank drains	CAR 04.635
cooling system drains	CAR 04.643
fuel tank drains	CAR 04.628
Locking devices	CAAM 04.4020-1
Log book required for MAC airplanes	CAR 04.510
Long columns	ANC-5 1.511
Longitudinal balance requirements, power off	CAR 04.704(b)
power on	CAR 04.704(a)
Looping, ground	CAR 04.708
Lubrication of hinges	CAAM 04.422-1a
systems	CAR 04.63
drains	CAR 04.635
gage	CAR 04.633
oil temperature	CAR 04.636
piping	CAR 04.634
tank	CAR 04.632
tank installation	CAR 04.631
Lugs, tension, aluminum alloy	ANC-5 5.52
steel	ANC-5 4.53
strength of	ANC-5 Table 4-10
m, correction of, for aspect ratio	CAAM 04.129-B2
defined	CAR 04.2121
M, formulas for	CAAM 04.1-C12
MAC, determination of	CAAM 04.217C-3e
determination of for biplanes	CAAM 04.217E-1, 04.217E-2
distance from base-line	CAAM 04.217D-3g
magnitude	CAAM 04.217D-3h

MAG-MOM

Magnafluxing of castings	CAAM 04.4023-2
Magnesium alloy, properties of	ANC-5 Table 6-1
Mail compartments	CAR 04.465
Maneuverability requirements	CAR 04.703
Maneuvering, horizontal surfaces	CAAM 04.2211
load factor increment, Condition I	CAR 04. Fig. 3
loads, ailerons	CAR 04.2230
horizontal tail	CAR 04.2211
vertical tail	CAR 04.2220
vertical surfaces	GAAM 04.2220
Manifold exhaust, construction and installation	CAR 04.661
heating system near	CAR 04.665
pressure gage for flight mechanic	CAR 04.650
for NAC airplanes	CAR 04.510
Manifolding, cowling and firewall	CAR 04.66
Manual, aircraft operating	CAR 04.504
Maple, bearing strength of	ANC-5 2.502
Margin of safety, defined	CAAM 04.1.-A4
linear, defined	CAAM 04.1-A4a
non-linear, defined	CAAM 04.1-A4b
table of	CAAM 04.0327
Mass balance and flutter	CAAM 04.404-1
Material to be specified on drawings	CAAM 04.0320-2b
Materials, failure of	ANC-5 1.41
for details	CAAM 04.400
for fuel, oil, and cooling systems	CAR 04.630
mechanical properties of alloy steels	ANC-5 Tables 4-3, 4-4, 4-5
mechanical properties of stainless steel	ANC-5 Table 4-5
1025 steel	ANC-5 Table 4-2
quality of	CAR 04.400
Mechanic, flight, instruments for	CAR 04.650
Metal covered wings	CAR 04.416
Metals	ANC-5 3.0
and alloys, miscellaneous	ANC-5 6.0
Method of using materials	ANC-5 3.01
Modifications by person other than holder of certificate	
major	CAAM 04.0613
minor	CAAM 04.0612
of primary structure	CAAM 04.0611
Modified Euler formula for short columns	CAAM 04.041
Modulus of elasticity, shear, defined (G)	ANC-5 1.512
tensile defined (E)	ANC-5 1.351
rigidity (G) defined	ANC-5 1.331
rupture, bending defined	ANC-5 1.351
bending of chrome-molybdenum steel tubes	ANC-5 1.414
torsional, of alloy steel tubes	ANC-5 Fig. 4-10
torsional, of aluminum alloy round tubes	ANC-5 Fig. 4-12
torsional, of 1025 steel tubes	ANC-5 Fig. 5-7
secant, (E_s) defined	ANC-5 Fig. 4-11
tangent, (E_t) defined	ANC-5 1.331
Moisture trapping pockets	ANC-5 1.331
Moment coefficient, mean effective	CAAM 04.4014-1
mean effective, with flaps	CAAM 04. Fig. 20
	CAAM 04.217D-31, 04.217D-

3j

MDM-OPE

Moment arm of objects with distributed parts	CAAM 04.0322-3c
Moments of inertia of solid circular sections	ANC-5 Table 8-2
Monoplane wings, internally braced, with flaps wire braced	CAAM 04.2140-1 CAR 04.4100
Motor, see "engine"	
Mount, engine, see "engine"	
N, subscript, defined	CAAM 04.129-A2
n, defined	CAR 04.119
()n, formula for	CAR 04.2121
n, formula for	CAAM 04.1-C14
NAC, non-airline carriers, equipment for	CAR 04.51
Nacelles, design conditions for	CAR 04.260, 04.261, 04.261G, 04.262
drag loads from	CAAM 04.217-C1
effect of drag of, in producing local loads	CAAM 04.31-B3
effect of on C_D	CAAM 04.217-A3
thrust loads from	CAAM 04.217-C2
Natural frequency, determination of	CAAM 04.323-3
dispersion of	CAAM 04.323-8 CAR 04.4636
Navigation instruments	CAR 04.5804
installation	CAAM 04.323-7
Nodes, location of	CAAM 04. Fig. 18
Normal force coefficient, determination of	CAAM 04.43-12
Nose wheel, steering system	CAAM 04.240-2
type landing gear	CAAM 04.340-E
tests of	CAAM 04.0320-2a
Nuts, dimensions to be given on drawings	CAAM 04.4020-2
elastic stop, restrictions on use of	
Oil-canning of wings	CAAM 04.416-1, 04.416-2
Oil coolers in equipment list	CAAM 04.0322-3f
drains	CAR 04.635
filler openings	CAR 04.637
gage	CAR 04.633
measuring devices to be shown on drawings	CAAM 04.0320-2g
piping	CAR 04.634
pressure gage for NAC airplanes	CAR 04.510
provisions for expansion of in drawings	CAAM 04.0320-2f
standard weight of	CAR 04.90
system	CAR 04.63
tank in equipment list	CAAM 04.0322-3b
installation	CAR 04.631
temperature	CAR 04.636
thermometer for NAC airplanes	CAR 04.510
One wheel landing	CAR 04.244
Operation limitations	CAR 04.74
airspeed	CAR 04.743
center of gravity limitations	CAR 04.742
powerplant	CAR 04.744
provisional weight	CAR 04.741
R aircraft	CAAM 04.031-5, 04.031-6
manual, aircraft	CAR 04.604
weight	CAR 04.740
restriction of, in flight	CAR 04.210
test	CAR 04.331

	OVE-PIN
Overflow from fuel tank	CAR 04.6290
Overhang ratio for double internal drag trussing	CAR 04.412
P, defined	CAR 04.105
p, formula for	CAAM 04.1-C4
Paints for protection	CAAM 04.4014-1
Panel point loads, computation of	CAAM 04.36-B1
Panels, curved	ANC-5 1.62
edge compression of	ANC-5 1.620
in shear	ANC-5 1.621
stiffened	ANC-5 1.712
stiffened in shear	ANC-5 1.722
ultimate strength of	ANC-5 1.623
under combined loadings	ANC-5 1.622
flat	ANC-5 1.61
buckling stresses of	ANC-5 1.610
rectangular, critical stress factors for	ANC-5 Fig. 1-5
rectangular, interaction curves for	ANC-5 Fig. 1-6
stiffened	ANC-5 1.711
stiffened in shear	ANC-5 1.721
ultimate strength of	ANC-5 1.612
under combined loading	ANC-5 1.611
with stiffeners, effective width of	ANC-5 Fig. 1-7
Parachutes, standard weight of	CAR 04.90
worn during test	CAR 04.7202
Parts, aluminum alloy	ANC-5 5.0
steel	ANC-5 4.5
wood	ANC-5 2.5
Passenger compartments, ventilation of	CAR 04.467
loads	CAR 04.264
seats, fastening of	CAR 04.464
Passenger and crew, weight of	CAR 04.90
Peening, use of	CAAM 04.43-6
Performance characteristics of airline carriers	CAR 04.73
omitted from three view drawing	CAAM 04.0320(g)
operation limitations	CAR 04.74
requirements	CAR 04.7, 04.70
modified for airline carriers	CAR 04.71
tests	CAR 04.72
Phase relationship between vibrating parts determination of	CAAM 04.323-6
Photographs of critical structures	CAAM 04.0328
substitution of for TC drawings	CAR 04.0320e
Piano hinges	CAAM 04.422-1e
Pilot compartments	CAR 04.463
in plane of propeller	CAR 04.4630
seating arrangement	CAR 04.4635
test	CAR 04.720
Pins, clevis, for hinge pins	CAR 04.4220
quality of	CAR 04.4020
steel, shearing strength, area and moment of inertia	ANC-5 Table 4-8
with locking devices	CAAM 04.432-1

PIP-PRO

Piping, cooling	CAR 04.642
fuel	CAR 04.625
oil	CAR 04.534
Pitch controls	CAR 04.6512
indicator, for ACP airplanes	CAR 04.532
stops for controllable	CAR 04.610
Placards for baggage compartment	CAR 04.465
in full view of pilot	CAR 04.4632
limits, in installation of new engine	CAAM 04.0612-B6, CAAM 04.0612-B7
Plastic instability failure defined	ANC-5 1.420
Plating for protection	CAAM 04.4014-1
Play in control system joints, and flutter	CAAM 04.404-1
Plywood covered wings	CAAM 04.311-E1, ANC-5 2.23
strength of	ANC-5 Table 2-2
webs, allowable stresses for	ANC-5 2.220
shear moduli for	ANC-5 2.221
Poisson's ratio, defined	ANC-5 1.321
related to shear and tension modulus of elasticity	ANC-5 1.351
Polarity of electrodes for arc welding	CAAM 04.4012-1c
Position indicator for wheels	CAAM 04.444
lights, installation	CAR 04.5827
Power, design (P) defined	CAR 04.105
loading, design ($\frac{N}{A}$) defined	CAR 04.107
off, balance requirements	CAR 04.704(b)
on, balance requirements	CAR 04.704(a)
Powerplant installation	CAR 04.6
cooling	CAR 04.64
engines	CAR 04.60
fuel systems	CAR 04.62
instruments, controls and accessories	CAR 04.65
lubrication systems	CAR 04.63
manifolding, cowling, firewall	CAR 04.66
materials	CAR 04.690
miscellaneous	CAR 04.69
propellers	CAR 04.61
limitations	CAR 04.744
Pressure, barometric, for sensitive altimeters	CAR 04.532
dynamic, defined	CAR 04.118
manifold, for NAC airplanes	CAR 04.510
Primary instability failure of columns	ANC-5 1.51
column curves	ANC-5 Fig. 1-3
discussion of	ANC-5 1.52
Production certificate, see part .01	CAR 04.002
Proof of structure	CAAM 04.3
of wings	CAAM 04.31
Propeller axes not in plane of symmetry	CAR 04.2230a, 04.2220a, 04.2223a
in plane of door	CAR 04.4610
in plane of pilot and control units	CAR 04.4630
pitch controls	CAR 04.6512

	PROP-RET
Propellers, certificated airworthy	CAR 04.61
clearance of	CAR 04.611
controllable pitch	CAR 04.610
reinforcements near	CAR 04.466
specified in equipment lists	CAAM 04.0322-3a
vibration characteristics	CAR 04.61
Properties, compressive	ANC-5 1.34
mechanical, explanation of tables of	ANC-5 3.0
of materials, alloy steels	ANC-5 Tables 4-3, 4-4, 4-5
aluminum alloys (17S)	ANC-5 Tables 5-2, 5-3, 5-4
aluminum alloys (24S)	ANC-5 Tables 5-5, 5-6
aluminum alloys (52S)	ANC-5 Table 5-7
1025 steel	ANC-5 Table 4-2
of plywood	ANC-5 Table 2-2
of woods, compressive	ANC-5 Table 2-1, 1.34
shear	ANC-5 1.35
tensile	ANC-5 1.3E
Proportional limit, illustrated on diagram	ANC-5 Fig. 1-1
in shear (F_{sp}) defined	ANC-5 1.352
tensile, (F_{tp}) defined	ANC-5 1.332
Protection of primary structure	CAAM 04.4014, CAR 04.4014
Provisional weight	CAR 04.71
Pull up speed factor	CAR 04. Fig. 2
Pulleys in control system	CAR 04.430
Pump system for more than one tank	CAR 04.621
used in fuel system	CAR 04.620
q, defined	CAR 04.118
formulas for	CAAM 04.1-C2
R, classification	CAAM 04.031-5
subscript, defined	CAAM 04.129-A2
Radiators, mounting of	CAR 04.641
Radio direction finder for ACP airplanes	CAR 04.532
equipment approved	CAR 04.503
equipment installation	CAR 04.583
for ACP airplanes	CAR 04.530
for NAC airplanes, instrument day	CAR 04.513
for NAC, visual contact night	CAR 04.512
in equipment list	CAAM 04.0322-3c
Rate of climb indicator for ACP airplanes	CAR 04.530
for NAC airplanes	CAR 04.513
Rate of turn and bank indicator for ACP airplanes	CAR 04.532
indicator, gyroscopic for NAC airplanes	CAR 04.513
Ratio, load, use of in combined loadings	ANC-5 1.424
Poisson's	ANC-5 1.321
stress, use of, in combined loading	ANC-5 1.424
Redundant structures	CAR 04.310
Repair, change or alteration of certificated airplanes	CAR 04.060
Restraint coefficient of chord members of metal spars	CAAM 04.311-C4
coefficient of webs of metal spars	CAAM 04.311-C5
Retractable landing gear, performance characteristics	
with	CAR 04.7320

Retracting mechanism	RETR-SAF
lock	CAAM 04.444
manual operation of	CAR 04.4440
wheels	CAR 04.444
Revision by person other than holder of certificate	CAR 04.444
major	CAAM 04.0613
minor	CAAM 04.0612
of drawings	CAAM 04.0611
of primary structure	CAAM 04.0320(f)
Rheostat for dimming instrument lights	CAAM 04.041
Rho, () defined	CAR 04.5826
Ribs, loadings, test	CAR 04.108
Ribs, spacing of	CAAM 04.313B
strength of	CAAM 04.416-2
test requirements	CAR 04.313
Rigging information for NAC airplanes	CAAM 04.313A
loads	CAR 04.510
loads, on tail and control surfaces	CAAM 04.266, CAR 04.266
Riveted joints in aluminum alloys	CAAM 04.32-2
bearing	ANC-5 5.50
shear	ANC-5 5.501
Rivets, bearing strength of steel sheets	ANC-5 5.500
dimensions to be given on drawings	ANC-5 Table 4-9
in tension	CAAM 04.0320-2a
joints with, in steel, allowable shear stress	CAAM 04.432-1
joints with, in steel, allowable bearing stress	ANC-5 4.500
properties of aluminum alloy	ANC-5 4.501
shearing strength of, steel area and moment of	ANC-5 Tables 5-8, 5-11
inertia	ANC-5 Table 4-8
Rockwell number, defined	ANC-5 3.00-(16)
Rudder arm, defined	CAAM 04.222-h
control system, loads on	CAR 04.232
forces	CAR 04.222
effects of tab on	CAR 04.2223
Rudders, balancing of	CAAM 04.424-6b
Running load of generator	CAR 04.5830
Rupture, see failure	
S, defined	CAR 04.104
s, formula for	CAAM 04.1-C3
S _D , equivalent drag area, defined	CAAM 04.1-A3
S _{DT} , estimated total drag area	CAAM 04.1-A3a
S.A.E. steels, relation between hardness and tensile	
strength	ANC-5 Table 47
Safety belt loads on structure	CAR 04.2640
belts for NAC airplanes	CAR 04.510
loads on, and seat installation	CAR 04.464, 04.5890
sign or signal for ACP airplanes	CAR 04.530
equipment, installation	CAR 04.581
belts	CAR 04.5810
belt signal	CAR 04.5812
deicers	CAR 04.5812
fire extinguisher	CAR 04.5811
landing flares	CAR 04.5813
factor of, (j) defined	CAR 04.121
factors of, minimum	CAR 04.2122
yield	CAR 04.201

SAF-SHO

Safety, margin of, defined	CAAM 04.1-A4
ultimate factor of (j_u) defined	CAR 04.122
yield factor of (j_y)	CAR 04.123
Sand castings, aluminum alloy	ANC-5 Table 5-9
Scarf joints in wood	ANC-5 2.511
Schedule, sample, of airplane approval	CAAM 04. Fig. 1
Screws, quality of	CAR 04.4020
wood, in primary structure	CAR 04.4021
Seam welding, see welding	
Seams, welded, in steel, allowable load	ANC-5 4.511
Seaplane boat, bottom loading on step	CAR 04.256
landings	CAR 04.254
two wave	CAR 04.255
conversion of, to skiplane	CAAM 04.0612--o
float, landings, with side loads	CAR 04.253
with vertical reactions	CAR 04.252
float loads	CAR 04.257
on bottom	CAR 04.2570
Seaplanes, ACP equipment for	CAR 04.534
boat, buoyancy of	CAR 04.4500
water-tight compartments in	CAR 04.451
clearance of propellers in	CAR 04.611
climb requirements for	CAR 04.7120
NAC equipment for	CAR 04.515
protection from deterioration	CAR 04.4014
take-off requirements for	CAR 04.7011
Seats	CAR 04.5890
fastening of passenger	CAR 04.464
Seaming loads	CAR 04.2590
Secant modulus (E_s) defined	ANC-5 1.331
Sections, thin-walled	ANC-5 1.6
Sediment trap and drain for fuel system	CAR 04.526
Sensitive altimeter for ACP airplanes	CAR 04.532
for NAC airplanes	CAR 04.513
Shackles in control system	CAR 04.432
Shear and bearing strength of aluminum alloy rivets	
and sheet	ANC-5 Table 5-11
buckling of curved panels under	ANC-5 1.621
buckling of flat panels under	ANC-5 Fig. 1-5
failure of material in	ANC-5 1.412
moduli for plywood webs	ANC-5 2.221
properties	ANC-5 1.35
general	ANC-5 1.350
modulus of elasticity defined	ANC-5 1.351
strength of stiffened curved panels	ANC-5 1.722
stresses in steel joints	ANC-5 4.500
Shearing of strength, area and moments of inertia of	
steel rivets, bolts, and pins	ANC-5 Table 4-8
Sheet, aluminum alloy, corrugated, column curves for	ANC-5 Fig. 5-3
alclad	ANC-5 Fig. 5-4
aluminum alloy, effective width constants	ANC-5 Table 1-1
aluminum alloy, strength with rivets	ANC-5 Table 5-11
stiffener combinations, effective widths of	ANC-5 Fig. 1-7
Shock absorbers, bending of	CAAM 04.44-1

SHOC-SPE

Shock absorption, landing	CAR 04.440, CAAM 04.440
taxing	CAR 04.441
Short columns	ANC-5 1.512
Shrinkage due to heat treatment, allowance for	CAAM 04.400-3
Sign conventions, for balancing	CAAM 04.218-B3
Signature of Authority representative(s)	CAAM 04.0328-1h
of checker	CAAM 04.0326
of company engineer(s)	CAAM 04.0328-1i
of computer	CAAM 04.0326
of manufacturing engineer(s)	CAAM 04.0328-1h
Single-cable controls	CAAM 04.437
Single engine dead, speed with	CAAM 04.2220
Ski landing gear	CAAM 04.240-3
model, approval of	CAAM 04.0612-C2
plane, approval of	CAAM 04.0612-C3
Skiplane, conversion of landplane to	CAAM 04.061-C
Skis, approval of	CAAM 04.061-B2
landing loads on	CAR 04.2410
Slip in joints in analysis of truss type spar	CAAM 04.311-C2
Slippage in joints, in wood beams	CAR 04.3114
Slip-stream effects on fabric covering	CAR 04.415
Slots, fixed, effect of on chord loads	CAAM 04.217-B3
Soldering in primary structure	CAR 04.4013
Spacing, longitudinal of bolts in wood	ANC-5 2.504
of bolts in spruce	ANC-5 Fig. 2-4
of bolts in wood, transverse	ANC-5 2.504
Span distribution curve, to determine resultant air	
force	CAAM 04.217D-3c
of C_M for wings, illustrated	CAAM 04. Fig. 16, Fig. 17
of wing load	CAAM 04.217-A
force distribution over, to determine resultant	
air force	CAAM 04.217D-3d
Spar, front, loading	CAAM 04.31-A
when spar does not extend to wing tip	CAAM 04.31-A3
low margin of safety in tension flange or	
chord	CAAM 04.21310-1a
see Condition I	
location effect on drag truss load	CAAM 04.31-B2b
metal	CAAM 04.311-B
thin web	CAAM 04.311-D
truss type	CAAM 04.311-C
rear, when C_M is small	CAAM 04.21310-1b
wood	CAAM 04.311-A
Spars, spruce, allowable stresses in	ANC-5 Fig. 2-2
Special devices for lateral control	CAR 04.226
Specifications, issuance of	CAR 04.0640
Speed definitions	
flap, design (V_f)	CAR 04.114
gliding, design (V_g)	CAR 04.112
indicated (V)	CAR 04.110
level, design (V_L)	CAR 04.111
stalling, design (V_S)	CAR 04.113
true air (V_t)	CAR 04.109
vertical maximum (V_m)	CAR 04.115

STEEL-STRES

Steel tubes, Johnson formulas for	ANC-5 1.512
1028, column curves for	ANC-5 Fig. 4-1
torsional modulus of rupture of round alloy	ANC-5 Fig. 4-12
tubing, chrome-molybdenum, bending modulus of	
rupture of	ANC-5 Fig. 4-10
chrome-molybdenum, column curves for	ANC-5 Figs. 4-2, 4-5,
	4-6, 4-7, 4-8, 4-9
under combined loads	ANC-5 4.4
Steering system for nose wheel,	CAAM 04.43-12
Step landing	CAR 04.254
Stiffened thin-walled sections, see "thin-walled"	
Stiffness, correction factors for computing	CAAM 04.311-B2
of metal beams	CAAM 04.311-B1
of primary structure	CAR 04.202
of truss type metal spars	CAAM 04.311-C2
Stops for adjustable stabilizer	CAR 04.421
for controllable pitch mechanism	CAR 04.610
for control surfaces	CAAM 04.421
for control system	CAAM 04.431, CAR 04.431
for elevator tabs	CAR 04.4210
Storage battery, see Battery	
Strain, axial, defined	ANC-5 1.320
lateral, defined	ANC-5 1.321
shearing	ANC-5 1.322
Strainers, fuel	CAR 04.626
Streamline tubing, properties of	ANC-5 Fig. 8-2
section of	ANC-5 Fig. 8-1
Strength, bearing, of bolts in wood	ANC-5 Fig. 2-3
of materials	CAAM 04.400-1
of plywood	ANC-5 Table 2-2
of primary structure	CAR 04.200
of woods	ANC-5 Table 2-1
ratio, computation of	ANC-5 1.425
shearing, of rivets, bolts and pins	ANC-5 Table 4-8
specifications, use of	ANC-5 1.02
tensile, relationship to hardness	ANC-5 4-7
Stress concentration, failure from	ANC-5 1.416
concentrations	CAR 04.3001
crippling of crushing (F_{cc})	ANC-5 1.531
defined	ANC-5 1.31
factors for buckling of flat rectangular panels	ANC-5 Fig. 1-5
normal and shear defined	ANC-5 1.311
ratios, use of in combined loading	ANC-5 1.424
strain diagram defined	ANC-5 1.330
strain diagrams, typical	ANC-5 Fig. 1-1
ultimate, tensile, defined (F_{tu})	ANC-5 1.334
compressive (F_{cu})	ANC-5 1.341
yield, defined, tensile (F_{ty})	ANC-5 1.333
Stressed skin fuselage, analysis of	CAAM 04.36-D
wings	CAAM 04.311-E
Stresses, allowable, for spruce spars	ANC-5 Fig. 2-2
buckling	ANC-5 1.610
column, for solid spruce struts	ANC-5 Fig. 2-1
combined, failure from	ANC-5 1.416
formula for combined	ANC-5 1.22
in plywood webs	ANC-5 2.220
simple unit, formulas for	ANC-5 1.21

	SPEED-STEEL
Speed, landing	CAR 04.700
limitations	CAR 04.743
maneuvering, design (V_p)	CAR 04.116
maximum in performance tests	CAR 04.722
see airspeed	
Spinning, abnormal	CAR 04.7060
large aircraft	CAR 04.706
requirements	CAR 04.706
Splice methods in control cables	CAAM 04.43-5
Splices in oil system	CAR 04.634
Sponson loads	CAR 04.2590
Spot welding, see welding	
Spring devices in control system	CAR 04.435
Spruce columns, primary failure of	ANC-5 2.10
distance between bolts in	ANC-5 Fig. 2-4
spars, allowable stresses in	ANC-5 Fig. 2-2
struts, solid, allowable column stresses for	ANC-5 Fig. 2-1
torsional properties of	ANC-5 2.31
Stability requirements	CAR 04.706
water	CAR 04.452
Stabilizer, adjustable, control for	CAAM 04.43-9
stops for	CAR 04.421
tension in control system	CAAM 04.43-1
balancing loads	CAR 04.2210
damping	CAR 04.2212
Stainless steel cable, strength of	ANC-5 Table 4-11
steel, properties of	ANC-5 Table 4-6
Standard symbols	CAAM 04.1-B
weights	CAR 04.90
Statement of conformity	CAR 04.0530
Static balance of controls	CAAM 04.424
elimination of	CAR 04.532
Steel, alloy, heat treated round tubing, column curves	
for	ANC-5 Fig. 4-4
properties of	ANC-5 Tables 4-3, 4-4, 4-5
beams, see beams	
cable, strength of	ANC-5 Table 4-11
columns, see columns	
general properties	ANC-5 4.0
joints, fittings, and parts	ANC-5 4.5
relation between hardness and tensile strength of	ANC-5 Table 4-7
rivets, bolts, and pins, shearing strength,	
moments of inertia, area of	ANC-5 Table 4-8
sheets, bearing strength of, on rivets	ANC-5 Table 4-9
stainless, mechanical properties of	ANC-5 Table 4-6
streamline tubing, chrome-molybdenum, column	
curves	ANC-5 Fig. 4-3
1024, properties of	ANC-5 Table 4-2
round tubing, torsional modulus of rupture of	ANC-5 Fig. 4-11
tie rods and tension lugs	ANC-5 Table 4-10
tie rods, lugs, and cables	ANC-5 4.53
torsion in	ANC-5 4.3
tubes, column formulas for	ANC-5 Table 4-1

STRU-SYM

Structural allowance for large engine	CAAM 04.0612-B9
analysis	CAAM 04.0327, CAR 04.0327
combined with tests	CAAM 04.301, CAR 04.301
proof of	CAR 04.300
changes	CAR 04.0535d
drawings for TC	CAAM 04.0320-2h
inspection	CAAM 04.041
for airworthiness	CAR 04.041
for TC	CAR 04.051
loading conditions	CAAM 04.2, CAR 04.2
See "Conditions"	
report TC	CAAM 04.0326, CAR 04.0326
tests	CAAM 04.3022
Structure, changes in	CAAM 04.041
primary	CAR 04.131
bolts, pins, screws in	CAR 04.4020
brazing and soldering in	CAR 04.4013
castings in	CAR 04.4023
deformation of	CAR 04.201
effect of wing-tip floats	CAR 04.2580
fittings in	CAR 04.271
proof of fittings and joints in	CAR 04.37
protection against deterioration	CAR 04.4014
stiffness of	CAR 04.202
strength of	CAR 04.200
tie rods and wires in	CAR 04.403
welding in	CAR 04.4012
proof of	CAR 04.3
redundant	CAR 04.310
to which safety belts are attached	CAR 04.2640
Struts, air loads on	CAR 04.267
column formula for solid wood	ANC-5 1.512
in internally braced biplanes	CAR 04.414
jury	CAR 04.4102
lift, local crushing of	CAR 04.4102
spruce, column curves for	ANC-5 Fig. 2-1
Studs to be locked	CAAM 04.432-1
Sump for fuel tank	CAR 04.622
Surfaces, horizontal, balancing loads	CAAM 04.2210
damping loads	CAAM 04.2212
maneuvering loads	CAAM 04.2211
tab effect loads	CAAM 04.2213, Fig. 23
vertical, damping loads	CAAM 04.2221
gust loads	CAAM 04.2222
maneuvering loads	CAAM 04.2220
Surging in fuel tanks, baffles to prevent	CAR 04.622
Switch, master	CAR 04.5828
Switches for landing lights	CAR 04.5825
ignition	CAR 04.6511
Symbols for stresses in metals	ANC-5 3.00
standard	CAAM 04.1-B
standard structural	ANC-5 1.1
Symmetrical flight conditions, flaps extended	CAR 04. Table 2
flaps retracted	CAR 04.1

TAB-TAK

Tab controls	CAAM 04.435, CAR 04.435
control system	CAAM 04.234, CAR 04.234
effects, Horizontal surfaces	CAAM 04.2213, CAR 04.2213
vertical surfaces	CAR 04.2223
ailerons	CAR 04.2231
limit loads on	CAR 04.225
loading conditions	CAAM 04. Fig. 23
position indicator	CAR 04.4350
Tables, explanation of mechanical properties	ANC-5 3.0
IV, and V, modifications of	CAAM 04.31-A3
Tab and computation of C_B	CAAM 04.424-4a
and flutter	CAAM 04.404-1
balancing of	CAAM 04.424-6d
controls for	CAAM 04.435
control systems for	CAAM 04.234
general	CAAM 04.426
installation	CAR 04.426
prevention of over-balance of	CAR 04.4210
stops on elevator	CAR 04.4210
Tachometer installation for flight mechanic	CAR 04.650
required for NAC airplanes	CAR 04.510
Tail, detail design of	CAAM 04.42
load distribution, damping	CAR 04. Fig. 6
maneuvering	CAR 04. Fig. 5
proof of	CAAM 04.32, CAR 04.32
surface balancing	CAAM 04.427, CAR 04.427
elevators	CAR 04.4271
rudders	CAR 04.4270
surface, clevis pins in hinges	CAR 04.4220
hinges, bearing on torque tubes	CAR 04.422
installation	CAR 04.420
stops for horizontal	CAR 04.421
surfaces, balancing distribution horizontal	CAR 04. Fig. 4
detail design of	CAR 04.42
horizontal balancing loads	CAR 04.2210
damping loads	CAR 04.2212
loading conditions for	CAR 04. Table 7
maneuvering loads	CAR 04.2211
tab effects	CAR 04.2213
vertical, damping loads	CAR 04.2221
gust loads	CAR 04.2222
loading conditions	CAR 04. Table 4
maneuvering loads	CAR 04.2220
wheel	CAAM 04.443
definition	CAR 04.4421
installation of	CAAM 04.0611-2
model	CAR 04.442
side loads on	CAAM 04.246, CAR 04.246
type gear	CAAM 04.240-1
wheels and skids, tests of	CAAM 04.340-D
Take-off, AC	CAR 04.732
emergency fuel pump for use in	CAR 04.520
excessive, in R type aircraft	CAAM 04.031-5a
requirements	CAR 04.701
landplanes	CAR 04.7010
seaplanes	CAR 04.7011

TAKE-TEST

Take-off requirements with retractable landing gear	CAR 04.7320
Tangent modulus (E_t) defined	ANC-5 1.351
Tank capacity and feed, fuel	CAR 04.620
construction, fuel	CAR 04.622
dump valves for	CAR 04.6270
fuel, plate showing capacity of	CAR 04.4631
gage for	CAR 04.624
installation, fuel	CAR 04.621
oil	CAR 04.631
capacity of	CAR 04.630
strength, fuel	CAR 04.623
Tanks, wing, empty	CAAM 04.2164
Tape	CAAM 04.415-1
Taper ratio, defined	CAAM 04.217-A1
Temperature effects on elastic stop nuts	CAAM 04.4020-2d
effects on rigging	CAAM 04.43-1
Tensile properties, general	ANC-5 1.33
stress-strain diagram	ANC-5 1.330
modulus of elasticity	ANC-5 1.331
proportional limit, defined (F_{tp})	ANC-5 1.332
strength versus hardness of S.A.E. steels	ANC-5 Table 4-7
stress-strain diagram	ANC-5 Fig. 1-1
ultimate stress, defined	ANC-5 1.334
illustrated	ANC-5 Fig. 1-1
yield stress (F_{ty}) defined	ANC-5 1.333
Tension failure	ANC-5 1.411
in control system	CAAM 04.43-1
Terminal efficiency of steel cables	ANC-5 4.530
Tests conducted in presence of Authority representative	CAR 04.3023
drop, of landing gear	CAR 04.340
energy absorption	CAAM 04.340, CAR 04.340
flight	CAAM 04.0532
for airworthiness	CAR 04.042
for performance	CAR 04.720
for TC	CAR 04.0534
load	CAR 04.304
report	CAR 04.0532
load	CAR 04.302, 04.3020
of ribs	CAAM 04.313
required	CAR 04.304
see also	CAR 04.126, 04.127, 04.200, 04.201
on similar structures	CAAM 04.301
proof	CAR 04.127
proving	CAR 04.734
reports of	CAAM 04.0328
TC	CAR 04.0328
results of, corrected to standard	CAR 04.7203
strength	CAR 04.126
structural, acceptable methods for	CAAM 04.3022-1
to be approved by Authority	CAAM 04.3022-2
vibration	CAAM 04.323
when using different materials from those specified for structure	CAR 04.3021

Thermometer, free air, for ACP airplanes	CAR 04.532
oil, for NAC airplanes	CAR 04.510
water, for NAC airplanes	CAR 04.510
Thimbles in control system	CAR 04.432
Thin-walled circular cylinders	ANC-5 1.63
curves panels	ANC-5 1.62
cylinders, aluminum alloy	ANC-5 5.211
elliptical cylinders	ANC-5 1.64
flat panels	ANC-5 1.61
sections, corrugated	ANC-5 1.73
edge compression	ANC-5 1.71
edge compression on curved panels	ANC-5 1.712
edge compression on flat panels	ANC-5 1.711
general	ANC-5 1.70
shear	ANC-5 1.72
on curved panels	ANC-5 1.722
on flat panels	ANC-5 1.721
stiffened	ANC-5 1.7
unstiffened	ANC-5 1.6
truncated circular cones	ANC-5 1.65
Thin-web, beams, aluminum alloy	ANC-5 5.23
Thread specified	CAAM 04.415-1
Three moment equation, in proof of control surfaces	CAAM 04.32-1
point landing	CAR 04.242
drop test	CAAM 04.340-B2
Throttle controls	CAR 04.6510
controls, special, in equipment lists	CAAM 04.0322-3e
Thrust load	CAAM 04.217-C2
propeller, unsymmetrical	CAR 04.2163
Tie-rods and wires	CAAM 04.403
minimum size of	CAR 04.403
steel	ANC-5 4.53
strength of	ANC-5 Table 4-10
Tire deflection, in drop tests	CAAM 04.340-B6
Tires acceptable	CAR 04.443
specially constructed	CAR 04.4430
Title page	CAAM 04.0326
sample	CAAM 04. Fig. 5
Tolerances of details	CAAM 04.400-2
Torque combined with high angle of attack	CAR 04.261, 04.2610
computation of	CAAM 04.36-C2a
loads	CAR 04.260
of engine, effect on fuselage analysis	CAAM 04.36-C2
tubes used as hinges, factor of safety	CAR 04.276
Torsion at elastic axis	CAAM 04.31-C
in aluminum alloy tubes	ANC-5 5.3
allowable shear stress	ANC-5 5.31
general	ANC-5 5.30
in circular thin-walled cylinders	ANC-5 1.632
in control surfaces	CAAM 04.42-1
in circular thin-walled truncated cones	ANC-5 1.657
in elliptical thin-walled cylinders	ANC-5 1.642
in fabric covered wings	CAAM 04.41-1
in steel	ANC-5 4.3
allowable shear stress in	ANC-5 4.31
failure of steel tubes	ANC-5 4.30

TORS-UNS

Torsion in truss type fuselage	CAAM 04.36-C
in wood, discussion	ANC-5 2.3
Torsional instability failures	ANC-5 1.423
modulus of rupture of aluminum alloy round tubing	ANC-5 Fig. 6-3
modulus of rupture of round steel alloy tube	ANC-5 Fig. 4-12
modulus of rupture of 1025 steel round tubing	ANC-5 Fig. 4-11
properties of spruce	ANC-5 2.31
shear stresses in aluminum alloy	ANC-5 5.31
Travel of control elements	CAAM 04.43-2
Truss, drag, double	CAR 04.412
multiple strand cable in	CAR 04.4120
lift, analysis of	CAAM 04.31-D
multiple strand wire in	CAR 04.4101
rear, when C_{M_a} is small	CAAM 04.21310-1b
single	CAAM 04.2135-3
transmitting landing loads	CAR 04.412
Tubes, aluminum alloy in bending	ANC-5 5.210
and compression	ANC-5 5.40
and torsion	ANC-5 5.41
and torsion and compression	ANC-5 5.42
round, material properties correction factors	ANC-5 Fig. 1-4
correction factors for	ANC-5 Fig. 1-4
formulas for steel, Johnson	ANC-5 1.512
round steel, in bending	ANC-5 4.210
and compression	ANC-5 4.41
and compression and torsion	ANC-5 4.42
in torsion	ANC-5 4.31
torque, used as hinges	CAR 04.276
Tubing, allowable column stress for 1025 steel	ANC-5 Fig. 4-1
chrome-moly	ANC-5 Fig. 4-2
chrome-moly streamline	ANC-5 Fig. 4-3
heat treated alloy round	ANC-5 Fig. 4-11
bending modulus of rupture of chrome-molybdenum	
steel	ANC-5 Fig. 4-10
properties of round	ANC-5 Table 8-1
streamline	ANC-5 Fig. 8-2
section of	ANC-5 Fig. 8-1
strength of chrome-moly round steel	ANC-5 Figs. 4-5, 4-6, 4-7, 4-8, 4-9
torsional modulus of rupture of round alloy	ANC-5 Fig. 4-12
torsional modulus of rupture of 1025 steel, round	ANC-5 Fig. 4-11
Turn-over, provision for	CAR 04.460
Type certificate, see certificate	
U, defined	CAR 04.117
Unapproved equipment, R aircraft	CAAM 04.031-6a
Ultimate strength of curved panels	ANC-5 1.623
flat panels	ANC-5 1.612
stress, compressive (F_{cu}), defined	ANC-5 1.341
shear, defined	ANC-5 1.353
tensile, (F_{tu}), defined	ANC-5 1.334
illustrated	ANC-5 Fig. 1-1
Universal joints	CAAM 04.432-2
Unsymmetrical flight conditions	CAAM 04.2150, CAR 04.215
propeller thrust	CAR 04.2163

V - W

V, defined	CAR 04.110
V _f , defined	CAR 04.114
limiting value of	CAR 04.211
V _g , defined	CAR 04.112
limiting values of	CAR 04.211
V _i , formulas for	CAAM 04.1-C19
V _L , corresponding to design power	CAR 04.211
defined	CAR 04.111
V _{La} , formula for	CAAM 04.1-C16
V _m , defined	CAR 04.115
formula for	CAAM 04.1-C18
V _p , defined	CAR 04.116
limiting values of	CAR 04.211
V _s , defined	CAR 04.113
formula for	CAAM 04.1-C17
V _{sf} , defined	CAR 04.113
V _t , defined	CAR 04.109
Vacuum gage for ACP airplanes	CAR 04.532
Values, standard, and formulas	CAAM 04.1-C
Valves, dump	CAR 04.6270
fuel	CAR 04.627
Varnish for protection	CAAM 04.4014-1
Vent, air, for fuel tanks	CAR 04.622
Ventilation of battery	CAR 04.5821
of passenger compartments	CAR 04.467
of pilot's compartment	CAR 04.463
Vertical surfaces, see surfaces	
tail surfaces, damping loads	CAR 04.2221
gust loads	CAR 04.2222
maneuvering loads	CAR 04.2220
special cases	CAR 04.2224
tab effects	CAR 04.2223
Vibrating parts, determination of phase relationship	
between	CAAM 04.323-6
Vibration and flutter	CAR 04.707
effect of on analysis	CAR 04.3001
failure of fuel tanks, prevention of	CAR 04.623
of cooling system piping	CAR 04.642
of engine propeller combination	CAR 04.61
of fuel lines	CAR 04.625
of radiators	CAR 04.641
protection against	CAR 04.4014
surface reinforced against, near propeller	CAR 04.466
see torque	
tests	CAAM 04.323, CAR 04.323
Vibrator for tests	CAAM 04.323-2
location of for tests	CAAM 04.323-4
Vickers number, defined	ANC-5 3.00-(17a)
Vision for pilot	CAR 04.463, 04.4633
Voltage for various gages of material	CAAM 04.4012-1d
variation of arc welder	CAAM 04.4012-1c
W, defined	CAR 04.100
w, formula for	CAAM 04.1C13

	W -WES
<u>W</u> , defined	CAR 04.107
<u>P</u>	
<u>W</u> , defined	CAR 04.106
<u>S</u>	
Water clearance of propellers	CAR 04.611
handling characteristics	CAR 04.708
loads	CAR 04.25
ability of structure to distribute	CAR 04.35
stability	CAAM 04.452, CAR 04.452
Water-tight compartments in boat seaplanes	CAR 04.451
compartments in seaplane floats	CAR 04.4500
doors	CAR 04.451d
Weather broadcast receiver for ACP airplanes	CAR 04.532
Web and flange area for gluing	ANC-5 2.512
plywood, see plywood	
Webs of truss type sprars, design of	CAAM 04.311-C5
loads in	CAAM 04.311-C3
strength of	CAR 04.3112
with axial load	CAR 04.3113
Weight, accuracy of in equipment list	CAAM 04.0322-3g
and balance report	CAAM 04.0531
for TC	CAR 04.0531
preliminary for TC	CAAM 04.0323
(W) defined	CAR 04.100
design, defined	CAR 04.101
increase in, allowance for	CAAM 04.0327
maximum authorized, NAC	CAR 04.740
minimum design, defined	CAR 04.1010
preliminary estimate of	CAR 04.0323
provisional, AC	CAR 04.741, 04.710,
	04.711
provisional, defined	CAR 04.103
standard, AC	CAR 04.710
standard, defined	CAR 04.102
table, TC	CAAM 04.0325, CAR04.0325
Weights, standard	CAR 04.90
Welded clusters	ANC-5 4.512
joints	ANC-5 4.51
allowable loads in	ANC-5 4.511
effect of welding on base metals	ANC-5 4.510
in aluminum alloys	ANC-5 5.51
parts, drawing of	CAAM 04.4012-1f
Welding, effects of, on analysis	CAR 04.3001
on base metal	ANC-5 4.510
on steel columns	ANC-5 4.102
electric	CAAM 04.4012
methods of control of	CAAM 04.4012-1e
in primary structure	CAR 04.4012
of control horns	CAAM 04.42-4
of hinges on torque tubes	CAAM 04.422-1d
spot and seam	CAAM 04.4012-2
torch	CAAM 04.4011, CAR 04.4011
Welds in control system	CAR 04.433
of fuel tanks	CAR 04.623
Westinghouse yield point defined	ANC-5 1.333

WHE-WIN

Wheels for landing gear in equipment list	CAR 04.442 CAAM 04.0322-2b, 04.0322-3d
main landing defined	CAR 04.4420
nose, defined	CAR 04.4421
position indicator for manual operation of	CAR 04.444 CAR 04.4441
retracting mechanism for lock	CAR 04.444 CAR 04.4440
side movement of in drop tests	CAAM 04.340-B4d
tail and tail skids, test of	CAAM 04.340-D
tail, defined	CAR 04.4421
Windows	CAR 04.4633
between pilot's compartment and cabin of pilot's compartment	CAR 04.4637 CAR 04.463
Windshields, easily opened of pilot's compartment	CAR 04.4633b CAR 04.4633
strength of	CAR 04.4633a
Wing, aileron and flap arrangement	CAR 04.413
area, design	CAAM 04.104
illustrated	CAAM Fig. 7
(S) defined	CAR 04.104
beam joints	CAAM 04.4110
beams, torsion in	CAR 04.411
cellules, indeterminate	CAAM 04.31-D3
chord, to determine resultant air forces	CAAM 04.217D-3b
drag truss	CAR 04.412
fabric covered, torsional stiffness of	CAAM 04.41-1
flap loadings	CAR 04.224
flaps	CAAM 04.224
installation to prevent flutter	CAR 04.425
load distribution	CAAM 04.217, CAR 04.217
across span	CAAM 04.217a
loading, design ($\frac{W}{S}$), defined	CAR 04.106
multiple strand cable in	CAR 04.4120
plan-form, to determine resultant air force	CAAM 04.217D-3a
strength deficient, R aircraft	CAAM 04.031-5b, 04.031-6c
struts for internally braced biplanes	CAR 04.414
tanks empty	CAAM 04.2164, CAR 04.2164
tip float loads	CAR 04.258
floats, effect on primary structure	CAR 04.2580
Wings, angular inertia of	CAAM 04.2150-1
boots, deflation of, deicers	CAR 04.5814
covering, fabric	CAR 04.415
metal	CAR 04.416
detail design of	CAAM 04.41
fabric covered, torsional stiffness	CAAM 04.41-1
internally braced monoplane, with flaps	CAAM 04.2140-1
lift truss	CAR 04.417
metal covered	CAAM 04.416, 04.311-E2
plywood covered	CAAM 04.311-E1, ANC-5 2.23
proof of	CAAM 04.31, CAR 04.31
stressed skin	CAAM 04.311-E
twisted, effect on resultant air forces	CAAM 04.217D-3h

WIR-YIELD

Wire anchorages	CAR 04.4031
braced monoplanes	CAR 04.4100
braced structure	CAR 04.4032
multiple strand	CAR 04.4101
sizes	CAR 04.4032
terminals, efficiency of	CAR 04.4030
Wires and tie rods	CAAM 04.403
at small angles	CAAM 04.274, CAR 04.274
bracing, redundant	CAAM 04.31-D2
drag, inspection of	CAAM 04.4015-1
in primary structure	CAR 04.403
non-parallel	CAR 04.315
parallel, double, factor of safety	CAR 04.273
streamline for lift bracing	CAR 04.410
Wood beams, joint slippage in	CAR 04.3114
general	ANC-5 2.
in primary structure, protection from deterioration	CAR 04.4014
propellers for light airplanes	CAR 04.61
<i>see particular reference desired as "beams", etc.</i>	
strength of	ANC-5 Table 2-1
torsion in	ANC-5 2.3
Woodruff keys in tubing	CAAM 04.432-3
Woods, strength of	ANC-5 Table 2-1
Workmanship for details	CAAM 04.400
quality of	CAR 04.400
Wrought metals, ultimate compressive stress of	ANC-5 1.341
X-raying of castings	CAAM 04.4023-2
Yield stress, column (F_{cc})	ANC-5 1.513
shear, illustrated	ANC-5 1.353
tensile, defined (F_{ty})	ANC-5 1.333
tensile, illustrated	ANC-5 Fig. 1-1