



<u>Center of Gravity (C.G.) Range</u>	Forward: 88.6" (2251mm) aft of datum at all weights Aft: 93.9" (2384 mm) aft of datum at 1764 lbs. (800kg) or less 93.0" (2362mm) aft of datum at 2039 lbs. (925 kg) Variation is liner between 1764 lbs. and 2039 lbs.
<u>Empty Weight C.G. Range</u>	None
<u>Datum</u>	80.4" (2043mm) forward of the wing leading edge at butt line 83.5" (2122 mm)
<u>Leveling Means</u>	Plumb bob from drilled bolt in cockpit overhead bow to center mark on forward undercarriage bay cross member.
<u>Maximum Weights</u>	Takeoff 2039 lbs. (925 kg.) Landing 2039 lbs. (925 kg.)
<u>Minimum Crew</u>	One pilot
<u>Number of Seats</u>	Two. Pilot Seat Arms seat forward 50.6" aft of datum seat aft 56.9" aft of datum Passenger Seat Arms seat forward 50.6" aft of datum seat aft 64.8" aft of datum
<u>Maximum Baggage</u>	100 lbs. (45 kg) at 82.3" (2090mm ) aft of datum
<u>Fuel Capacity</u>	Total 48.6 gallon (184 liters) (2 x 24.3 gal tanks at 91 mean fuel inch). Usable 48.1 gallon (182 liters). Refer to flight manual for fuel distribution weight and balance data. See Note 1.
<u>Oil Capacity</u>	Total Capacity 8 US quarts (7.6 liters) (6 US quarts useable) Oil arm 110.4" aft of datum See Note 1 for data on system oil.
<u>Maximum Operation Altitude</u>	15,000 feet AMSL
<u>Control Surface Movements</u>	Aileron Up 4.4" $\pm$ 0.2" at trailing edge Down 2.9" $\pm$ 0.2" at trailing edge  Elevator Up 6.3" + 0, -0.2" at trailing edge Down 3.3" $\pm$ 0.2" at trailing edge  Elevator fixed tabs Trailing edge of tabs 1.6" to 2" below plane of elevator upper surface  Rudder L & R 6.7" $\pm$ 0.2" at trailing edge  Wing flaps retracted 0° $\pm$ 1° first notch 20° $\pm$ 1° full 40° $\pm$ 1°

Manufacturer's Serial Numbers 070009 and SA01100, SA01101 and subsequent.  
A CASA Certificate of Airworthiness for Export must be submitted for each individual airplane. See "Import Requirements."

Import Requirements A United States airworthiness certificate may be issued on the basis of an Australian Export Certificate of Airworthiness signed by a representative of the Civil Aviation Safety Authority containing the following statement:  
"The aircraft covered by this certificate has been examined, tested and found to comply with the CASA approved Seabird Master Drawing List SBR 07/14 issue 3 or later revisions, approved under US Type Certificate No. A00070CE and to be in a condition for safe operation"

The U.S. airworthiness certification basis for this aircraft type certificated under FAR § 21.29 and exported by the country of manufacture is FAR § 21.183 (c).

Per 21.50(b), Instructions for Continued Airworthiness (ICA) complying with FAR 23.1529, must be furnished before delivery of the first airplane or issuance of a US standard certificate of airworthiness, whichever occurs later. (Note 4)

Certification Basis The regulations (unless otherwise stated) are Title 14 of the Code of Federal Regulations (14CFR):

1) FAR 21.29, 21.183(c) and FAR 23 dated February 1, 1965, as amended through Amendment 23-34 effective 2/17/87 with the exception of:

14 CFR part 23 sections 23.331, 23.445 and 23.1163 at Amendment 42;

14 CFR part 23 sections 23.993, 23.1103, 23.1147, 23.1193, 23.1322, 23.1385, 23.1387, 23.1389, 23.1391, 23.1393 and 23.1395 at Amendment 43;

14 CFR part 23 sections 23.251, 23.773, 23.1525, 23.1549 and 23.1557 at Amendment 45;

14 CFR part 23 sections 23.335, 23.371 and 23.572 at Amendment 48;

14 CFR part 23 sections 23.867, 23.1307, 23.1321, 23.1323, 23.1326, 23.1351, 23.1353, 23.1383 and 23.1401 at Amendment 49;

14 CFR part 23 sections 23.71, 23.145, 23.161, 23.201, 23.203, 23.1521, 23.1543, 23.1583, 23.1585, 23.1587 and 23.1589 at Amendment 50;

14 CFR part 23 sections 23.955, 23.1041, 23.1043, 23.1047, 23.1091, 23.1093, 23.1107, 23.1141, 23.1143, 23.1181, 23.1183, 23.1203 and 23.1337 at Amendment 51;

14 CFR part 23 sections 23.1305 at Amendment 52;

14 CFR part 23 sections 23.1308 at Amendment 57;

14 CFR part 23 sections 23,777, 23.853, 23.1301, 23.1303, 23.1309, 23.1310, 23.1311, 23.1331, 23.1431 and 23.1559 at Amendment 62.

2) 14 CFR Part 36, effective December 1969, including Amendments 36-1 through 36-30.

## 3) Equivalent Level of Safety per 21.21(b)(1):

- a) TC00381CE-A-S-1 dated May 16, 2016, Pitot Heat Indication System, § 23.1326 (b)(1) at amendment 23-49;
- b) TC00381CE-A-P-3 dated May 16, 2016, Fuel Quantity Indication, § 23.1337(b)(1) at amendment 23-51.

4) No Exemptions

5) No Special Conditions

6) The airplane is not approved for ditching

7) The airplane is not approved for flight into known or forecasted icing.

8) CASA issued CASA Amended Type Certificate No. VA502 on January 24, 1994 for this model and revised it on 5 May 2016 as identified on Revision 7 of CASA TCDS VA502.

Date of application for original FAA type certificate: January 10, 2011

Production Basis

None

Equipment

The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification. In addition the approved (for FAA) Flight Manual, document SBR 12/16 Issue date June 7, 2016 or later approved version, must be carried.

Service Information

Each of the documents listed below must state that it is approved by the Civil Aviation Safety Agency (CASA):

- Aircraft flight manuals, and
- Airworthiness Limitations Section of the Service Manual.

The FAA accepts such documents and considers them FAA-approved for type design data only unless one of the following conditions exists:

- The documents change the limitations, performance, or procedures of the FAA approved manuals; or
- The documents make an acoustical or emissions changes to this product's U.S. type certificate as defined in 14 CFR § 21.93.

The FAA uses the post type validation procedures to approve these documents. The FAA may delegate on case-by-case to CASA to approve on behalf of the FAA for the U.S. type certificate. If this is the case it will be noted on the document.

Available documents for the SB7L-360A model:

FAA approved Aircraft Flight Manual Document SBR 12/16 Issue date June 7, 2016, or later approved version, must be carried. (See Note 2)

Instructions for Continued Airworthiness (ICA) {AMM} Document SBR 10/16 Issue 1, dated June 7, 2016, or later accepted versions. Chapter 4 Airworthiness Limitations are dated June 7, 2016 (See Note 3 and Note 4)

II. SB7L-360A2 (Seeker) Approved June 7, 2016Engine

Textron Lycoming IO-390-A1B6  
Type Certificate: E00006NY

<u>Fuel</u>	Avgas 100LL (Blue) Avgas 100 (Green)		
<u>Engine Limits</u>	2700 rpm (No time limit).		
<u>Oil</u>	As specified in the latest revision of Textron Lycoming Service Instruction No.1014.		
<u>Propeller and Propeller Limits</u>	Seabird Aviation Model: Bishton BB177-70-55 Two bladed Fixed Pitch wooden, pusher FAA Type Certificate: P10BO Diameter: 69.7 in. (1770 mm). Pitch: 55.1 in. (1400 mm) at 29.5 in. (750 mm) radius.  Static rpm at full throttle: Maximum: 2450 rpm. Minimum: 2350 rpm.		
<u>Airspeed Limits</u>		(KIAS)	(KCAS)
	Never exceed ( $V_{NE}$ )	134	133
	Maneuvering ( $V_A$ )	107	105
	Max structural cruise ( $V_{NO}$ )	107	105
	Max flaps extended ( $V_{FE}$ )	95	93
<u>Center of Gravity (C.G.) Range</u>	Forward: 89.5" (2274mm) aft of datum at all weights  Aft: 94.8" (2409 mm) aft of datum at all weights.		
<u>Empty Weight C.G. Range</u>	None		
<u>Datum</u>	80.4" (2043mm) forward of the wing leading edge at butt line 83.5" (2122 mm)		
<u>Leveling Means</u>	Plumb bob from drilled bolt in cockpit overhead bow to center mark on forward undercarriage bay cross member.		
<u>Maximum Weights</u>	Takeoff	2147 lbs. (974 kg.)	
	Landing	2039 lbs. (925 kg.)	
<u>Minimum Crew</u>	One pilot		
<u>Number of Seats</u>	Two.		
	Pilot Seat Arms	seat forward	50.6" aft of datum
		seat aft	56.9" aft of datum
	Passenger Seat Arms	seat forward	50.6" aft of datum
		seat aft	64.8" aft of datum
<u>Maximum Baggage</u>	100 lbs. (45 kg) at 82.3" (2090mm ) aft of datum		
<u>Fuel Capacity</u>	Total 48.6 gallon (184 liters) (2 x 24.3 gal tanks at 91 mean fuel inch). Usable 48.1 gallon (182 liters). Refer to flight manual for fuel distribution weight and balance data. See Note 1.		

<u>Oil Capacity</u>	Total Capacity	8 US quarts (7.6 liters) (6 US quarts useable)	
	Oil arm	110.4" aft of datum	
	See Note 1 for data on system oil.		
<u>Maximum Operation Altitude</u>	15,000 feet AMSL		
<u>Control Surface Movements</u>	Aileron	Up	4.4" $\pm$ 0.2" at trailing edge
		Down	2.9" $\pm$ 0.2" at trailing edge
	Elevator	Up	6.3" + 0, -0.2" at trailing edge
		Down	3.3" $\pm$ 0.2" at trailing edge
	Elevator fixed tabs	Trailing edge of tabs 1.6" to 2" below plane of elevator upper surface	
	Rudder L & R	6.7" $\pm$ 0.2" at trailing edge	
	Wing flaps	retracted	0° $\pm$ 1°
		first notch	20° $\pm$ 1°
		full	40° $\pm$ 1°
Manufacturer's Serial Numbers	SA02100 and subsequent. A CASA Certificate of Airworthiness for Export must be submitted for each individual airplane. See "Import Requirements."		
Import Requirements	<p>A United States airworthiness certificate may be issued on the basis of an Australian Export Certificate of Airworthiness signed by a representative of the Civil Aviation Safety Authority containing the following statement: "The aircraft covered by this certificate has been examined, tested and found to comply with the CASA approved Seabird Master Drawing List SBR 07/14 issue 3 or later revisions, approved under US Type Certificate No. A00070CE and to be in a condition for safe operation"</p> <p>The U.S. airworthiness certification basis for this aircraft type certificated under FAR § 21.29 and exported by the country of manufacture is FAR § 21.183 (c).</p> <p>Per 21.50(b), Instructions for Continued Airworthiness (ICA) complying with FAR 23.1529, must be furnished before delivery of the first airplane or issuance of a US standard certificate of airworthiness, whichever occurs later. (Note 4)</p>		
<u>Certification Basis</u>	<p>The regulations (unless otherwise stated) are Title 14 of the Code of Federal Regulations (14CFR):</p> <p>1) FAR 21.29, 21.183(c) and FAR 23 dated February 1, 1965, as amended through Amendment 23-34 effective 2/17/87 with the exception of:</p> <p>14 CFR part 23 sections 23.331, 23.445 and 23.1163 at Amendment 42;</p> <p>14 CFR part 23 sections 23.993, 23.1103, 23.1147, 23.1193, 23.1322, 23.1385, 23.1387, 23.1389, 23.1391, 23.1393 and 23.1395 at Amendment 43;</p>		

14 CFR part 23 sections 23.251, 23.773, 23.1525, 23.1549 and 23.1557 at Amendment 45;

14 CFR part 23 sections 23.335, 23.371 and 23.572 at Amendment 48;

14 CFR part 23 sections 23.867, 23.1307, 23.1321, 23.1323, 23.1326, 23.1351, 23.1353, 23.1383 and 23.1401 at Amendment 49;

14 CFR part 23 sections 23.71, 23.145, 23.161, 23.201, 23.203, 23.1521, 23.1543, 23.1583, 23.1585, 23.1587 and 23.1589 at Amendment 50;

14 CFR part 23 sections 23.955, 23.1041, 23.1043, 23.1047, 23.1091, 23.1093, 23.1107, 23.1141, 23.1143, 23.1181, 23.1183, 23.1203 and 23.1337 at Amendment 51;

14 CFR part 23 sections 23.1305 at Amendment 52;

14 CFR part 23 sections 23.1308 at Amendment 57;

14 CFR part 23 sections 23.777, 23.853, 23.1301, 23.1303, 23.1309, 23.1310, 23.1311, 23.1331, 23.1431 and 23.1559 at Amendment 62.

2) 14 CFR Part 36, effective December 1969, including Amendments 36-1 through 36-30.

3) Equivalent Level of Safety per 21.21(b)(1):

- c) TC00381CE-A-S-1 dated May 16, 2016, Pitot Heat Indication System, § 23.1326 (b)(1) at amendment 23-49;
- d) TC00381CE-A-P-3 dated May 16, 2016, Fuel Quantity Indication, § 23.1337(b)(1) at amendment 23-51.

4) No Exemptions

5) No Special Conditions

6) The airplane is not approved for ditching

7) The airplane is not approved for flight into known or forecasted icing.

8) CASA issued CASA Amended Type Certificate No. VA502 on September 24, 2013 for this model and revised it on 5 May 2016 as identified on Revision 7 of CASA TCDS VA502.

Date of application for FAA for the SB7L-360A2 model: March 10, 2014

Production Basis

None

Equipment

The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification. In addition the approved (for FAA) Flight Manual, document SBR 13/16 or later approved version, must be carried.

Service Information

Each of the documents listed below must state that it is approved by the Civil Aviation Safety Agency (CASA):

- Aircraft flight manuals, and
- Airworthiness Limitations Section of the Service Manual.

The FAA accepts such documents and considers them FAA-approved for type design data only unless one of the following conditions exists:

- The documents change the limitations, performance, or procedures of the FAA approved manuals; or

- The documents make an acoustical or emissions changes to this product's U.S. type certificate as defined in 14 CFR § 21.93.

The FAA uses the post type validation procedures to approve these documents. The FAA may delegate on case-by-case to CASA to approve on behalf of the FAA for the U.S. type certificate. If this is the case it will be noted on the document.

Available documents for the SB7L-360A2 model:

FAA approved Aircraft Flight Manual Document SBR 13/16 Issue date June 7, 2016 or later approved version, must be carried. (See Note 2)

Instructions for Continued Airworthiness (ICA) {AMM} Document SBR 11/16 Issue 1, dated June 7, 2016, or later accepted versions. Chapter 4 Airworthiness Limitations are dated June 7, 2016. (See Note 3 and Note 4)

NOTES

- NOTE 1 A current weight and balance report including a list of equipment included in the certificated empty weight and loading instructions when necessary must be provided for each aircraft at the time of original certification. The certificated empty weight and the corresponding center of gravity location must include full oil and unusable fuel (17.5 pounds at 106.9 inches).
- NOTE 2 Airplane operation must be in accordance with the CASA-approved Aircraft Flight Manual listed above. All placards listed in Section 2 of the FAA approved AFM must be displayed in the appropriate locations. The US versions of the SB7L-360A and SB7L-360A2 AFM limitations may not be changed without CASA and direct FAA approval.
- NOTE 3 Mandatory retirement lives, required inspections, and inspection intervals of components are contained in the Airworthiness Limitations Section (Chapter 4) of the Airplane Maintenance Manual dated June 7, 2016 are part of (SB7L-360A model Doc: SBR10/16 Issue 1 or later versions) and (SB7L - 360A2 model Doc: SBR 11/16 Issue 1 or later versions). The US versions of the SB7L-360A and -360A2 limitations may not be changed without CASA and direct FAA approval.
- NOTE 4 August 12, 2016, the FAA accepted the complete set of ICAs which includes the previously approved ALS section of the ICA, chapter 4, dated June 7, 2016 for both models.

...END....