

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

A46NM
Revision 4
Airbus Industrie
A330-202
A330-301
A330-223
A330-321
A330-322
A330-323

March 21, 2000

FAA TYPE CERTIFICATE DATA SHEET NO. A46NM

This data sheet which is part of Type Certificate No. A46NM prescribes conditions and limitations under which the product for which the Type Certificate was issued meets the airworthiness requirements of the US Federal Aviation Regulations.

Type Certificate Holder: Airbus Industrie
1, Rond-Point Maurice Bellonte
31707 Blagnac
France

I. Type A330-200 Series Transport Category Airplanes:

Airbus A330-202 - approved March 31, 1998:

Airbus A330-223 - approved June 21, 1999:

A330-202: Definition of reference airplane by Airbus Industrie Documents:
FAA A330-202 Type Design, ref. AI/EA-N 415.0531/98 Issue 3, dated
May 25, 1998, for type definition and Type Certification Standard Equipment List, ref.
00G000A0102/COS.

A330-223: Definition of reference airplane by Airbus Industrie Documents:
FAA A330-223 Type Design, ref. AI/EA-N 415.1223/98 Issue 2, dated
August 20, 1998, for type definition and Type Certification Standard Equipment
List, ref. 00G000A0123/COS.

Engines:

Airplane Model	Engine Model	Engine Type Certificate
A330-202	Two GE-CF6-80E1A4 turbojet engines	FAA-Type Certificate E41NE
A330-223	Two PW 4168A turbojet engines	FAA-Type Certificate E36NE

Fuel:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Page no.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Rev. no.	4	2	2	2	2	4	3	3	3	3	2	4	3	4	4	4	4	4

Engine Limits:

Engine Limitations	A330-202 CF6-80E1A4 FAA Data Sheet E41NE	A330-223 PW 4168A FAA Data Sheet E36NE
Static Thrust at Sea Level • Take-off (5 mn) ¹ (flat rated 30° C) • maximum continuous (flat rated 25° C)	66,870 lbs 60,400 lbs	68,600 lbs 59,357 lbs
Maximum Engine Speed • N1 rpm (%) • N2 rpm (%)	3,835 (115.5%) 11,105 (113%)	3,600 10,450
Maximum Gas Temperature • Take-off (5mn) ¹ • Maximum Continuous • Starting ²	1,787° F (975° C) 1,724° F (940° C) 1,598° F (870° C)	1,157° F (625° C) 1,112° F (600° C) 1,148° F (620° C)
Maximum Oil Temperature (Supply Pump Outlet) °C • Continuous Operation • Transient (15 mn max.) • Minimum Oil Pressure (PSI)	320° F (160° C) 347° F (175° C) 10.0 psid (69 KPa)	325° F (163° C) 350° F (177° C) 70.0 psid (482.6 KPa)
Approved oils	Brand Names: See GE Service Bulletin 79-001 Specification: See GE specification D50TF1, Class B	Oils conforming to P&W Turbojet engine Service Bulletin 238, latest revision.

Table references:

- (1) 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go around).
 (2) 4 consecutive cycles of 2 minutes each.

- Maximum Operating Limit Speed/Mach, V_{MO}/M_{MO} 360 KIAS / .86 M
- Design Diving Speed, V_D 365 KIAS / .93 M
- Design Maneuvering Speed, V_A Refer to AFM Limitations Section
- Maximum Flaps/Slats Extended Speed or Operating Speed, V_{FE} :

Configuration	Slats/Flaps/Ailerons °	V_{FE} (kt)	
1	16/0/0	240	Intermediate Approach
	16/8/0	215	Take-off
1 + F	16/8/5	205	Take-off
2	20/14/10	196	Take-off and Approach
3	23/22/10	186	Take-off, Approach, and Landing
FULL	23/32	180	Landing

- Minimum Control Speed, V_{MC} Refer to AFM Performance Section (Performance Engineering Program/OCTOPUS)

Landing Gear Speeds:

- Maximum Speed with Landing Gear Operating (Extension and Retraction), V_{LO} 250 KIAS/.55M
- Maximum Speed with Landing Gear Locked Down, V_{LE} 250 KIAS/.55M
- Tire Limit Speed (Ground Speed) 203 KIAS (235mph)

Center of Gravity Limits:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Datum:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Leveling Means:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Maximum Weight:

Variant	020 (Basic) kg/lb
Maximum Take-off Weight, MTOW	230,000/507, 150
Maximum Landing Weight, MLW	180,000/396,900
Maximum Zero Fuel Weight, MZFW	168,000/370,440

Minimum Crew:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Number of Seats:

The maximum number of passengers approved for emergency evacuation is:
375 passengers with a 3 pairs of Type A and 1 pair Type 1 exits configuration, and
379 passengers with a 4 pairs of Type A exits configuration.

Maximum Baggage:

Cargo Compartment	Maximum Load (kg/lb)
Forward	18,869/41,606
Aft	15,241/33,606
Rear	3,468/7,646

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weight) see weight and Balance Manual: Airbus Industrie Document 00G080A0006/C2S for A330-200 airplanes.

Fuel Capacity:

	3 Tank Airplane			
	Usable	Fuel	Unusable	Fuel
Tank	liters	gallons	liters	gallons
Wing	91,300	24,121	348	70
Center	41,560	10,980	83	21.9
Trim Tank	6,230	1,646	6	1.6
Total	139,090	36,746	437	115.5

Maximum Operating Altitude:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Control Surface Movements:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Manufacturer's Serial Numbers:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Import Requirements:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Certification Basis (A330-200):

- a. Part 25 of the FAR effective February 1, 1965, including the following:
- Amendments 25-1 through 25-63, amendments 25-65, 25-66, 25-68, 25-69, 25-73, 25-75, 25-77, 25-78, 25-81, 25-82, 25-84 and 25-85
 - § 25.851 as amended by amendment 25-74
 - The following sections of Part 25 of the FAR as amended through amendment 25-72:
- | | |
|---------------------------------------|-------------|
| FAR 25.21 | FAR 25.693 |
| FAR 25.29 | FAR 25.723 |
| FAR 25.111 | FAR 25.729 |
| FAR 25.147 | FAR 25.731 |
| FAR 25.177 | FAR 25.733 |
| FAR 25.181 | FAR 25.735 |
| FAR 25.205 | FAR 25.772 |
| FAR 25.307 | FAR 25.779 |
| FAR 25.331 | FAR 25.783 |
| FAR 25.341 | FAR 25.933 |
| FAR 25.343 | FAR25.979 |
| FAR 25.345 | FAR 25.1093 |
| FAR 25.351 | FAR 25.1381 |
| FAR 25.361 | FAR 25.1419 |
| FAR 25.373 | FAR 25.1522 |
| FAR 25.395 | FAR 25.1533 |
| FAR 25.397 | FAR 25.1543 |
| FAR 25.415 | FAR 25.1551 |
| FAR 25.459 | FAR 25.1581 |
| FAR 25.571 (b) | FAR 25.1583 |
| FAR 25.613 (Vertical stabilizer only) | FAR 25.1587 |
| FAR 25.615 (Vertical stabilizer only) | |
- b. Part 25 of the FAR amendment 25-64 with the following exceptions:
- Cockpit seats will not meet FAR 25.562 amendment 25-64 but will meet FAR 25.561
 - Compliance with 25.785(a), (b), and (c) at amendment 25-64 for front row seats in front of a bulkhead will be based on ensuring a 35 inch free head strike envelope.
- c. In accordance with § 21.16 of the FAR, the following special conditions are part of the original A330 certification basis, and were published in the Federal Register April 15, 1993, (Docket No. NM-75, Special Conditions No. 25-ANM-69), and are also be part of the A330-200 certification basis:
- (1) Operation without Normal Electrical Power
 - (2) Electronic Flight Control System (EFCS) failures and Mode Annunciation
 - (3) Command Signal Integrity
 - (4) Protection From Lightning and Unwanted Effects of High Intensity Radiated Fields (HIRF)
 - (5) Interaction of Systems and Structures
 - (6) Design Dive Speed
 - (7) Design Maneuver Requirements
 - (8) Limit Pilot Forces
 - (9) Tail plane Tank Emergency Landing Loads
 - (10) Limit Engine Torque
 - (11) Flight Characteristics
 - (12) Flight Envelope Protection
 - (13) Side Stick Controllers
 - (14) Computerized Airplane Flight Manual (AFM) Performance Information
- d. Part 34 of the FAR, effective September 10, 1990, including Amendment 34-1.
- e. Part 36 of the FAR, effective December 1, 1969, including Amendments 36-1 through 36-21.

- f. The technical requirements are complemented by the following guidance material:
 For precision approach and landing,
 1. AC 120-29
 2. AC 120-28C
 and for the automatic flight control system
 1. AC 20-57A for automatic landing
 2. AC 25.1329-1A for cruise
- g. Equivalent safety findings have been made in accordance with FAR 21.21(b)(1) for the following paragraphs of the FAR:
- (1) 25.335(d) for design airspeeds
 - (2) 25.345 for high lift devices
 - (3) 25.349 for control surface loads
 - (4) 25.351(b) for unsymmetrical loads
 - (5) 25.371 for gyroscopic loads
 - (6) 25.373 for speed control devices
 - (7) 25.101(I); 25.105(c)(1); 25.109(a)(b)(c)(d)(e)(f); 25.113(a)(b)(c); 25.115(a); 25.735(f)(g)(h)(b) for rejected takeoff and landing performance
 - (8) 25.933(a)(1)(ii), 25.1309(b)(1) for flight critical thrust reverser
- h. Optional requirements elected:
- 25.801 for ditching.
 - 25.1419 for icing.

Note: Compliance with the FAA Required Modification List for Airbus Model A330 Aircraft as included under the Import Requirements section of TCDS Revision 4, dated March 21, 2000 or later TCDS revision, is necessary for an A330 aircraft to be found in a condition for safe operation.

Production Basis:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Equipment:

- The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification.
- The following Airbus Industrie Documents defines the set of modifications which comprise the FAA certificated type design. These documents contains certain modifications determined necessary for FAA certification, including installation of ozone converters, fuel system improvements and thrust reverser modifications.
 - AI/EA-N 415.0531/98 Issue 3, dated May 25, 1998 for the A330-202
 - AI/EA-N 415.1223/98 Issue 2, dated August 20, 1998 for the A330-223
- Equipment approved for installation is listed in the Certification Standard Equipment List
 - 00G000A0102/C0S for the A330-202.
 - 00G000A0123/C0S for the A330-223.
- Cabin furnishings, equipment and arrangement shall conform to the following specification:
 - 00F252K0005/C01 for cabin seats.
 - 00F252K0006/C01 for galley.
 - 00F252K0020/C01 for cabin attendant seats

Other Information Applicable to A330-200 Series Airplanes:

Hydraulic Fluids:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Auxiliary Power Unit (APU):

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Tires:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Airplane Flight Manual:

Airplane operation must be in accordance with the DGAC-Approved Airplane Flight Manual (AFM), US version, listed below, applicable to the specific airplane model and serial number.

Model A330 Aircraft	Airbus Industrie Document Refr.	Revision No.	Date
-202	AI/ST-F 33000	2	January 6, 1999
-223	AI/ST-F 33000	2	January 6, 1999

Service and Operating Information:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Notes:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

II. Airbus A330-300 Series Transport Category Airplanes:**Airbus A330-301 - approved October 21, 1993:****Airbus A330-321 - approved June 21, 1999:****Airbus A330-322 - approved June 21, 1999:****Airbus A330-323 - approved October 8, 1999:**

- A330-301: Definition of reference airplane by Airbus Industrie Document: AI/EA-N 415.1181/96 Issue 3, dated July 16, 1997 for type definition and 00G000A0101/C0S for equipment list.
- A330-321: Definition of reference airplane by Airbus Industrie Document: AI/EA-N 415.1184/96 Issue 3, dated June 25, 1998 for type definition and 00G000A0121/C0S for equipment list.
- A330-322: Definition of reference airplane by Airbus Industrie Document: AI/EA-N 415.1183/99 Issue 3, dated June 25, 1998 for type definition and 00G000A0121/C0S for equipment list.
- A330-323: Definition of reference airplane by Airbus Industrie Document: AI/EA-N 415.1630/99 Issue 1, dated July 20, 1999 for type definition and 00G000A0123/C3S for equipment list.

Engines:

Airplane Model	Engine Model	Engine Type Certificate
A330-301	Two GE-CF6-80E1A2 turbojet engines	FAA-Type Certificate E41NE
A330-321	Two PW 4164 turbojet engines	FAA-Type Certificate E36NE
A330-322	Two PW 4168 turbojet engines	FAA-Type Certificate E36NE
A330-323	Two PW 4168A turbojet engines	FAA-Type Certificate E36NE

Fuel:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Engine Limits:

Engine Limitations	A330-301 CF6-80E1A2 FAA Data Sheet E41NE	A330-321 PW 4164 FAA Data Sheet E36NE	A330-322 PW 4168 FAA Data Sheet E36NE	A330-323 PW 4168A FAA Data Sheet E36NE
Static Thrust at Sea Level				
• Take-off (5 mn) ¹ (flat rated 30° C)	64,530 lbs	64,500 lbs	68,600 lbs	68,600 lbs
• maximum continuous (flat rated 25° C)	60,040 lbs	55,800 lbs	59,357 lbs	59,357 lbs
Maximum Engine Speed				
• N1 rpm (%)	3,835 (115.5%)	3,600 (101%)	3,600 (101%)	3,600 (101%)
• N2 rpm (%)	11,105 (113%)	10,450 (103%)	10,450 (103%)	10,450 (103%)
Maximum Gas Temperature				
• Take-off (5mn) ¹	1,787° F (975° C)	1,157° F (625° C)	1,157° F (625° C)	1,157° F (625° C)
• Maximum Continuous	1,724° F (940° C)	1,112° F (600° C)	1,112° F (600° C)	1,112° F (600° C)
• Starting ²	1,598° F (870° C)	1,148° F (620° C)	1,148° F (620° C)	1,148° F (620° C)
Maximum Oil Temperature (Supply Pump Outlet) °C				
• Continuous Operation	320° F (160° C)	325° F (163° C)	325° F (163° C)	325° F (163° C)
• Transient (15 mn max.)	347° F (175° C)	350° F (177° C)	350° F (177° C)	350° F (177° C)
• Minimum Oil Pressure (PSI)	10.0 psid (69 KPa)	70.0 psid (482.6 KPa)	70.0 psid (482.6 KPa)	70.0 psid (482.6 KPa)
Approved oils	See SB CFMI 79-001 or GE specification D50TF1 Class B	See P&W Service Bulletin 238, latest revision.		

Table references:

- (1) 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around).
(2) 4 consecutive cycles of 2 minutes each

Airspeed Limits (Indicated Airspeed, IAS, unless otherwise stated):

- Maximum Operating Limit Speed/Mach, V_{MO}/M_{MO} 360 KIAS / .86
- Design Diving Speed, V_D 365 KIAS / .93
- Design Maneuvering Speed, V_A Refer to AFM Performance Section
- Maximum Flaps/Slats Extended Speed or Operating Speed, V_{FE}

Configuration	Slats/Flaps/Ailerons °	V_{FE} (kt)	
1	16/0/0	240	Intermediate Approach
	16/8/0	215	Take-off
1 + F	16/8/5	205	Take-off
2	20/14/10	196	Take-off and Approach
3	23/22/10	186	Take-off, Approach, and Landing
FULL	23/32	180	Landing

- Minimum Control Speed, V_{MC} Refer to AFM performance Section.
(Performance Engineering Program/OCTOPUS)

Landing Gear Speeds:

- Maximum Speed with Landing Gear Operating (Extension and Retraction) V_{LO} 250 KIAS/.55M
- Maximum Speed with Landing Gear Locked Down, V_{LE} 250 KIAS/.55M
- Tire Limit Speed (Ground Speed) 203 KIAS(235mph)

Center of Gravity Limits: See Section III, Data pertinent to All A330-200 and A330-300 Models.

Datum: See Section III, Data pertinent to All A330-200 and A330-300 Models.

Leveling Means: See Section III, Data pertinent to All A330-200 and A330-300 Models.

Maximum Weight:

Model A330 Airplane Weight Variant	A330-301/-321/-322			A330-323
	000 (Basic) kg/lb	001 (MOD 42200) kg/lb	002 (MOD 42600) kg/lb	020 (Basic) kg/lb
Maximum Take-off Weight, MTOW	212,000/467,460	184,000/405,720	212,000/467,460	230,000/507,064
Maximum Landing Weight, MLW	174,000/383,670	174,000/383,670	177,000/390,285	185,000/407,856
Maximum Zero Fuel Weight, MZFW	164,000/361,620	164,000/361,620	167,000/368,235	173,000/381,400

Minimum Crew: See Section III, Data pertinent to All A330-200 and A330-300 Models.

Number of Seats:

The maximum number of passengers approved for emergency evacuation is:

375 passengers with a 3 pair Type A and 1 pair Type 1 exit configuration, and

379 passengers with a 4 pair Type A exit configuration.

Maximum Baggage:

Cargo Compartment	Maximum Load (kg/lb)
Forward	22,861/50,400
Aft	18,507/40,800
Rear	3,468/7,646

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weight) see Weight and Balance Manual Ref. 00G080A0006/C3S for A330-300 airplanes.

Fuel Capacity:

Model	Two Tank Airplane					
	Useable Fuel				Unusable fuel	
	A330-301/-321/-322		A330-323		All Models	
Tank	liters (kg)	gallons (lb)	liters (kg)	gallons (lb)	liters (kg)	gallons (lb)
Wing	91,056 (72,845)	24,054 (164,052)	91,764 (73,411)	24,241 (165,327)	348 (278)	70 (41)
Trim Tank	6,115 (4891)	1,614 (11,008)	6,121 (4897)	1,617 (11,028)	6 (4.8)	1.6 (11)
Total	97,171	25,669	97,885	25,858	354	88

Maximum Operating Altitude:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Control Surface Movements: *(Total one-way travel in each direction of each movable control surface on the aircraft.)*

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Manufacturer's Serial Numbers:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Import Requirements:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Certification Basis (A330-300):

- a. Part 25 of the FAR effective February 1, 1965, including the following:
 - Amendments 25-1 through 25-63, amendments 25-65, 25-66, 25-77
- b. Part 25 of the FAR amendment 25-64 with the following exceptions:
 - Cockpit seats will not meet FAR 25.562 amendment 25-64 but will meet FAR 25.561
 - Compliance with 25.785(a), (b), and (c) at amendment 25-64 for front row seats in front of a bulkhead will be based on ensuring a 35 inch free head strike envelope.
- c. FAA Special conditions issued for the A330 in accordance with Section 21.16 of the FAR and published in the Federal Register April 15, 1993, (Docket No. NM-75, Special Conditions No. 25-ANM-69), as follows:
 - (1) Operation without Normal Electrical Power
 - (2) Electronic Flight Control System (EFCS) failures and Mode Annunciation
 - (3) Command Signal Integrity
 - (4) Protection From Lightning and Unwanted Effects of High Intensity Radiated Fields (HIRF)
 - (5) Interaction of Systems and Structures
 - (6) Design Dive Speed
 - (7) Design Maneuver Requirements
 - (8) Limit Pilot Forces
 - (9) Tail plane Tank Emergency Landing Loads
 - (10) Limit Engine Torque
 - (11) Flight Characteristics
 - (12) Flight Envelope Protection
 - (13) Side Stick Controllers
 - (14) Computerized Airplane Flight Manual (AFM) Performance Information
- d. Special Federal Aviation regulation FAR Part 34, effective September 10, 1990.
- e. Part 36 of the FAR as amended by amendments 36-1 through 36-20.
- f. The technical requirements are complemented by the following guidance material:

For precision approach and landing,

 1. AC 120-29
 2. AC 120-28C

and for the automatic flight control system

 1. AC 20-57A for automatic landing
 2. AC 25.1329-1A for cruise
- g. Equivalent safety findings have been made in accordance with FAR 21.21(b)(1) for the following paragraphs of the FAR:
 - (1) 25.335(d) for design airspeeds
 - (2) 25.345 for high lift devices
 - (3) 25.349 for control surface loads
 - (4) 25.351(b) for unsymmetrical loads
 - (5) 25.371 for gyroscopic loads
 - (6) 25.373 for speed control devices
 - (7) 25.101(I); 25.105(c)(1); 25.109(a)(b)(c)(d)(e)(f); 25.113(a)(b)(c); 25.115(a); 25.735(f)(g)(h)(b) for rejected takeoff and landing performance
 - (8) 25.933(a)(1)(ii), 25.1309(b)(1) for flight critical thrust reverser
- h. Optional requirements elected:
 - 25.801 for ditching.
 - 25.1419 for icing.

Note: Compliance with the FAA Required Modification List for Airbus Model A330 Aircraft as included under the Import Requirements section of TCDS Revision 4, dated March 21, 2000 or later TCDS revision, is necessary for an A330 aircraft to be found in a condition for safe operation.

Production Basis:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Equipment:

- The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification.
- The following Airbus Industrie Documents defines the set of modifications which comprise the FAA certificated type design. This document contains certain modifications determined necessary for FAA certification, including installation of ozone converters, fuel system improvements and thrust reverser modifications.
 - AI/EA-N 415.1181/96 Issue 3, dated July 16, 1997 for the A330-301
 - AI/EA-N 415.1184/96 Issue 3, dated June 25, 1998 for the A330-321
 - AI/EA-N 415.1183/96 Issue 3, dated July 25, 1998 for the A330-322
 - AI/EA-N 415.1630/99 Issue 1, dated July 20, 1999 for the A330-323
- Equipment approved for installation is listed in the Certification Standard Equipment List
 - 00G000A0101/C0S for the A330-301.
 - 00G000A0121/C0S for the A330-321 and -322.
 - 00G000A0123/C3S for the A330-323.
- Cabin furnishings, equipment and arrangement shall conform to the following specification:
 - 00F252K0005/C01 for cabin seats.
 - 00F252K0006/C01 for galley.
 - 00F252K0020/C01 for cabin attendant seats

Other Information Applicable to A330-300 Series Airplanes:**Hydraulic Fluid:**

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Auxiliary Power Unit (APU):

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Tires:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Airplane Flight Manual:

Airplane operation must be in accordance with the DGAC-Approved Airplane Flight Manual (AFM), US version, listed below, applicable to the specific airplane model and serial number.

Model A330 Aircraft	Airbus Industrie Document Refr.	Revision No.	Date
-301	AI/EV-O 33000	3	January 6, 1999
-321, -322	AI/ST-F 33000	2	January 6, 1999
-323	AI/ST-F 33000	1	October 5, 1999

Service and Operating Information:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

Notes:

See Section III, Data pertinent to All A330-200 and A330-300 Models.

III. Data Pertinent to All A330-200 and A330-300 Models:**Fuel:**

Aircraft	Nomenclature	Specification		
		United States	France	United Kingdom
A330-202 A330-301	Kerosene (conform to GE specification D50TF2 with current exception of JP4 and JET B)	ASTM D 1655 (JET A) (JET A1)	AIR 3405C	DERD 2494/2453
A330-223 A330-321 A330-322 A330-323	Fuel and fuel additives conforming to the latest applicable issue of FAA approved Pratt & Whitney Turbojet Engine Service Bulletin 2016 may be used separately or mixed in any proportions without adversely affecting the engine operation or power output.			

(a) Additives: According to GE "Specific Operating Instructions", installation manual. The above mentioned fuels are also suitable for the APU.

Center of Gravity Limits:

Refer to DGAC-Approved Airplane Flight Manual, US Version, Limitations Section for center of gravity envelope. Note: 0% MAC is located 1359.59 in. (34.532m) from the datum line

Datum:

The aircraft reference zero datum point is located 251.29 in. (6.3825 m) forward of the nose section, 275.6 in. (7m) under the fuselage centerline (datum line).

Leveling Means:

Inclinometer on cabin seat track rails (refer to WBM chapter 1.80).

Minimum Crew:

2 - Pilots

Maximum Operating Altitude

41,100 feet (12,496 m) slats and flaps retracted (clean)
20,000 feet (6,096 m) Slats or, Slats/Flaps extended.

Control Surface Movements: *(Total one-way travel in each direction of each movable control surface on the aircraft.)*

Control Surface	Maximum Travel
Aileron	+25 /- 25°
#1 Spoilers	Speed Brake 23° Lift Dumper 35°
#2,3 Spoilers	Roll 35° Speed Brake 30° Lift Dumper 50°
#4,5,6 Spoilers	Roll 35° Speed Brake 30° Lift Dumper 50°
Aileron Droop	10°
Flaps	32°
Slats	23°
Stabilizers	+2°/-14°
Elevator	+15°/-30°
Rudder	+30°/-30°

Manufacturer's Serial Numbers/Production Basis:

A330 aircraft, all series and models, are produced in France under production approval FG 035 issued by the DGAC (on behalf of JAA) to Airbus Industrie.

Import Requirements:

To be considered eligible for operation in the United States, each aircraft manufactured under this certificate must be accompanied by a certificate of airworthiness for export containing a certifying statement endorsed by the exporting foreign civil airworthiness authority which states (in the English language): "The aircraft covered by this certificate has been examined, tested, and found to conform to the Type Design approved under Type Certificate No. A46NM as defined in TCDS A46NM revision 4 (or later revision) and to be in condition for safe operation."

The U.S. airworthiness certification basis for aircraft type certificated under FAR Section 21.29 and exported by the country of manufacture is FAR Section 21.183(c) or 21.185(c). The U.S. airworthiness certification basis for aircraft type certificated under FAR Section 21.29 exported from countries other than the country manufacture (e.g., third party country) is FAR Sections 21.183(d) or 21.185(b). These sections provide that U.S. airworthiness certificates are issued only if the Administrator finds "that the aircraft conforms to the type design and is in a condition for safe operation." Notwithstanding that FAR sections 21.183(d) and 21.185(b) do not specifically address or require certification by the foreign civil airworthiness authority of the country of manufacture, such certification is the only practical way for an applicant to show, and the FAA to find conformity to the FAA-approved type design and condition for safe operation. Additional guidance is contained in FAA Advisory Circular (AC) 21-23, Airworthiness Certification of Civil Aircraft, Engines, Propellers, and Related Products Imported into the United States.

FAA Required Modification List for Airbus Model A330 Aircraft:

Prior to issuance of a Standard Airworthiness Certificate on any Airbus A330 model aircraft, all modifications shown on the (Model A330) Required Modification List (RML) with compliance times already **past**, must be accomplished before the aircraft can be found to be in a condition for safe operation.

Note 1: RML modifications with compliance times already past means that relative to the date of issuance of an Airworthiness Certificate for an individual aircraft, the compliance time of the RML item in calendar time and/or flight hours and/or flight cycles has been exceeded.

All **future** required modifications shown on the RML must be incorporated into the operator's maintenance or inspection program prior to placement of the aircraft into operation [just as for future airworthiness limitation items (ALI's), life limited parts or Certification Maintenance Requirements (CMR's)]. These future RML modifications must be incorporated prior to the compliance time specified in the RML and must remain with the airplane records. In the event of any transfer of the airplane to another operator these RML requirements must continue to be complied with and incorporated into the new operator's maintenance program.

Note 2: Future RML modifications means that relative to the date of issuance of an Airworthiness Certificate for an individual aircraft, the compliance time of the RML item in calendar time and/or flight hours and/or flight cycles has not yet been exceeded.

Prior to issuance of a Standard Airworthiness Certificate on any Airbus A330 model aircraft, the following note must be placed on the Airworthiness Certificate:

"CONTINUED AIRWORTHINESS: Type Certificate Data Sheet (TCDS) A46NM, Revision 4, dated March 21, 2000, contains the "FAA Required Modification List (RML)" that must be complied with for this aircraft to remain in a condition for safe operation. The RML is part of the permanent record for this aircraft; it must remain with the aircraft data and continue to be complied with in the event of transfer to another operator."

Note 3: The RML was finalized through its publication in TCDS Revision 4 and requirements will not be added by later TCDS revisions. Therefore, the RML in TCDS A46NM Revision 4 or any later TCDS revision are equivalent and acceptable for compliance. All future modifications that the FAA determines must be accomplished on U.S. registered aircraft will be addressed by issuance of an Airworthiness Directive (AD).

Authority for these required modifications is given per the airworthiness certification provisions of 49 U.S.C. 44704 (c), which states "the Administrator may include in an airworthiness certificate terms required in the interest of safety". "Terms required in the interest of safety" include actions to correct unsafe conditions issued by the foreign authority of the state of design that also meet FAA criteria for corrective action. This law also gives the FAA the authority to adopt FAR § 21.183(c) and (d), which form the regulatory basis for the issue of standard U.S. airworthiness certificates on imported products. 14 CFR §21.183(c) and (d) provide that airworthiness certificates are issued only if the Administrator finds "that the aircraft conforms to the type design and is in a condition for safe operation." The modifications identified in the list below are required in the interest of safety and are necessary for this airplane to be in a condition for safe operation.

A Notice of Policy Statement announcing the FAA's policy with respect to foreign mandatory continued airworthiness information, when no aircraft of the affected design are currently operating in the U.S. was published in the Federal Register on May 11, 1998.

Alternative Methods of Compliance to an RML modification:

For each RML modification, an alternative method of compliance (AMOC) or adjustment of the compliance time may be used if approved by the Manager, International Branch, ANM-116, FAA Transport Airplane Directorate; 1601 Lind Avenue Southwest; Renton, Washington 98055; telephone (425) 227-2110; fax (425) 227-1149. Operators shall submit their request through an appropriate FAA Principle Maintenance Inspector, who may add comments and then send it to the Manager, International Branch.

An AMOC is not required to accomplish an RML modification in accordance with a DGAC-approved revision of an Airbus service bulletin later than that referenced in the RML. As discussed under the Service and Operating Information section of this TCDS, a service bulletin that contains a statement that the document is DGAC approved is accepted by the FAA and considered as FAA approved.

FAA Required Modification List(RML) for the Airbus Model A330 Aircraft:

The RML for the A330 is composed of items 1A through 40B as listed on the following pages.

RML #	DGAC CN #	Mod #	Mandatory Action	Applicable To:	S/B #	S/B REV(s)	Compliance Time
1A	1996-006-024(B)R1	42409	FUSELAGE - REINFORCE JOINT AT FRAMES 48 - 53.2	Airplanes without mod 43475 or without SB A330-21-3027	53-3015	1 or higher	Frames 53/53.1/53.2: Prior to 5800 total flight cycles. For frames 48 to 52: Prior to 15600 total flight cycles.
1B	1996-006-024(B)R1	42409	FUSELAGE - REINFORCE JOINT AT FRAMES 48 - 53.2	Airplanes with mod 43475 or with SB A330-21-3027	53-3015	1 or higher	Frames 53/53.1/53.2 prior to 5300 total flight cycles. For frames 48 to 52 prior to 14100 total flight cycles.
2	1997-265-056(B)R1	N/A	REVISE AMM AIRWORTHINESS LIMITS.	ALL Model A330 Airplanes	AMM CHAPTER 5	8 or higher	Prior to C of A Issuance
3	1998-539-088(B)	N/A	REPLACE FRANKENJURA EYE-END ON ELEVATOR SERVOCONTRLS	ALL Model A330 Airplanes	AOT 27-24	1 or higher	Prior to 7/09/99 or C of A Issuance; whichever occurs later
4	1999-111-093(B)	45870 AND 46231 AND 46891	INSTALL WIRING FOR E-BRAKE SHUTOFF VALVE	ALL Model A330 Airplanes	29-3054 AND 32-3083R2	3054: 0 or higher 3083: 2 or higher	Prior to 7/31/01 or C of A Issuance; whichever occurs later
5	1999-123-092(B)	43724, OR 44661, OR 44662	FLIGHT MANAGEMENT COMPUTER REPLACEMENT	ALL Model A330 Airplanes	22-3011, OR 22-3009, OR 22-3010	All SB's revision 1 or higher	Prior to 6/30/99 or C of A Issuance; whichever occurs later
6	1999-142-097(B)	46170, OR 46596	FLIGHT CONTROL UNIT CHANGE	Airplanes with Mod. 44887 OR with SB 22-3012	22-3021, OR 22-3020	1 or higher	Prior to 6/30/99 or C of A Issuance; whichever occurs later
7	1999-144-094(B)R1	45977	REPLACE RAT ACTUATOR	Airplanes with Sundstrand RAT	29-3057	1 or higher	Prior to 12/31/00 or C of A Issuance; whichever occurs later
8	1999-331-098(B)	42447	REPLACE NLG HINGE FITTING BRACKETS	ALL Model A330 Airplanes	52-3046	1 or higher	Prior to 01/21/01 or C of A Issuance; whichever occurs later

A330 Required Modification List (RML)

RML #	DGAC CN #	Mod #	Mandatory Action	Applicable To:	S/B #	S/B REV(s)	Compliance Time
9A	1999-350-100(B)R1	46904, AND 46905	REPLACE PIVOT PINS & BELLCRANK ASSEMBLIES	-202, -223,-243, -323, -343	32-3095	1 or higher	The Later of (a) and (b): (a) Prior to 4800 total flight cycles or within 5 years since new; which ever occurs first; and (b) Prior to 06/08/01
9B	1999-350-100(B)R1	46902, AND 46903	REPLACE PIVOT PINS & BELLCRANK ASSEMBLIES	ALL Model A330 Airplanes	32-3096	1 or higher	Prior to 10 years since new or C of A Issuance; whichever occurs later
9C	1999-350-100(B)R1	46904, AND 46905	REPLACE PIVOT PINS & BELLCRANK ASSEMBLIES	-301, -321, -322,-341, -342	32-3095	1 or higher	The Later of (a) and (b): (a) Prior to 6500 total flight cycles or within 5 years since new; which ever occurs first; and (b) Prior to 06/08/01
10A	1999-406-103(B)	45307	REPLACE HORIZONTAL HYDRAULIC BRACKET	All Airplanes, except -202, with mod 43475 OR with SB 21-3027	53-3088	0 or higher	Prior to 7880 total flight cycles or 30700 total flight hrs; whichever occurs first
10B	1999-406-103(B)	45307	REPLACE HORIZONTAL HYDRAULIC BRACKET	All Airplanes, except -202, without mod 43475 OR without SB 21-3027	53-3088	0 or higher	Prior to 8620 total flight cycles or 33600 total flight hrs; whichever occurs first
10C	1999-406-103(B)	45307	REPLACE HORIZONTAL HYDRAULIC BRACKET	-202	53-3088	0 or higher	Prior to 8540 total flight cycles or 33300 total flight hrs, whichever occurs first
11	1999-442-104(B)	46820, OR 46865	PASSENGER/ CREW DOOR FRAME LININGS	ALL Airplanes with mod 44461 OR 44462 OR 44463 OR 44464 OR 44465	25-3096	1 or higher	Prior to 11/03/05 or C of A Issuance; whichever occurs later
12A	1999-449-105(B)	45899	REINFORCE FRAME 40	-202, -223	53-3093	2 or higher	Prior to 9700 Total flight cycles or 28800 total flight hours; whichever occurs first
12B	1999-449-105(B)	45899	REINFORCE FRAME 40	-301, -321,-322, -341, -342	53-3093	1 or higher	Prior to 7320 total flight cycles or 26130 total flight Hours; whichever occurs first
13	1999-508-106(B)	41652, OR 43904	MODIFY LOWER SECTIONS OF FRAME 48 TO 53.2	ALL Model A330 Airplanes	53-3062	0 or higher	Prior to 2300 Total flight cycles or C of A Issuance; whichever occurs later
14	95-053-009(B)R3	44049	REPLACE HYDRAULIC SENSE LINES	Airplanes equipped with PW model 4164 or 4168 engines	29-3019	1 or higher	Prior to 10/31/97 or C of A Issuance; whichever occurs later
15	95-248-022(B)	42607	MOD - FUSELAGE STRINGER 39	ALL Model A330 Airplanes	53-3021	0 or higher	Prior to 3800 total flight cycles

A330 Required Modification List (RML)

RML #	DGAC CN #	Mod #	Mandatory Action	Applicable To:	S/B #	S/B REV(s)	Compliance Time
16	96-106-030(B)	41849 OR 43364	AFT CARGO COMPARTMENT DOOR	ALL Model A330 Airplanes	52-3023	0 or higher	Prior to 6000 total flight cycles
17	96-134- 031(B)R2 AND 97-266-057(B)	[45271]; OR [44143 AND SB- A330-32- 3070R0]	LANDING GEAR FREE FALL EXTENSION ELECTRIC CIRCUIT	ALL Model A330 Airplanes	[32-3048R3] OR [32-3048R0, R1 or R2 AND 32- 3070R0)	-3048:3 or higher, OR 3048: 0,1, or 2 AND 3070: 0 or higher	Prior to 3/23/99 or C of A Issuance; whichever occurs later
18	96-136- 032(B)R1	43689 AND 44603	ELECTRICAL POWER-APU FUEL PUMPS ELEC SUPPLY	ALL Model A330 Airplanes	28-3041	3 or higher	Prior to 3/1/98 or C of A Issuance; whichever occurs later
19	96-159- 033(B)R2	44173, OR 44237	MLG- SHORTENING MECHANISM BELLCRANK	ALL Model A330 Airplanes without Mod 43029 installed	32-3047	2 or higher	Prior to 1/07/99 or C of A Issuance; whichever occurs later
20	96-184- 036(B)R2	46558	ICE PROTECTION- WING ANTI ICE VALVES	ALL Model A330 Airplanes	S/B 30-3020	-3020: 0 or higher	Prior to C of A Issuance
21	97-004-041(B)	43697, OR 43761	REAR FUSELAGE CARGO DOOR FRAME	ALL Model A330 Airplanes	53-3048	0 or higher	Prior to 7000 total flight cycles
22	97-154- 049(B)R1	44457 AND 45022	RADIO ANTENNA ALTIMETER "THOMSON"	ALL Model A330 Airplanes fitted with Radio Altimeter P/N 9599-607-19501	34-3044 AND 21-3053 AND 92-3017	All S/Bs: 0 or higher	Prior to 10/31/98 or C of A Issuance; whichever occurs later
23	97-178-051(B)	44918	A/C RAM AIR OUTLET DUCT	ALL Model A330 Airplanes	21-3059	0 or higher	Prior to 6/30/98 or C of A Issuance; whichever occurs later
24	97-179-052(B)	45088, OR 45087	FWD FLAP TRACKS	ALL Model A330 Airplanes	57-3048	1 or higher	Prior to 3500 total flight hours
25	97-204-053(B)	41856, OR 45224	FWD FUSELAGE- REINFORCE DBLR/OUTFLOW VALVE	ALL Model A330 Airplanes	53-3084	0 or higher	Prior to 7500 total flight cycles
26	97-361- 058(B)R2	44511 AND 41671	MLG-SHORTENING MECHANISM BELLCRANK BOLTS	ALL Model A330 Airplanes without Mod 43029 installed	32-3056	1 or higher	Prior to 12000 total flight cycles on the MLG

A330 Required Modification List (RML)

RML #	DGAC CN #	Mod #	Mandatory Action	Applicable To:	S/B #	S/B REV(s)	Compliance Time
27	97-386-060(B)	45077 OR 45564	HOT TRANSFO- RECTIFIERS OPERATION	ALL Model A330 Airplanes	24-3019	1 or higher	Prior to 12/31/98 or C of A Issuance; whichever occurs later
28	98-022- 062(B)R1	46115	PNEUMATIC LEAK DETECTION SYSTEM WIRING	ALL Model A330 Airplanes	AOT 36-04 OR SB 36-3012	AOT: 0 or higher -3012: 0 or higher	Prior to 12/16/98 or C of A Issuance; whichever occurs later
29	98-023-063(B)	43441, OR 41848	CENTER FUSELAGE REINFORCE FR 53.3/53.5	ALL Model A330 Airplanes with Mod. 40161	53-3039	1 or higher	Prior to 10000 total flight cycles
30	98-024-064(B)	44360, OR 44440	REINFORCE KEEL ANGLE OF FRONT SPAR FR40	All Airplanes with Mod. 41652	57-3046	0 or higher	Prior to 4000 total flight cycles
31	98-098-065(B)	[42351AND 42353 AND 43438]; OR 41848	REINFORCE DOORFRAMES/ EMERGENCY EXITS	Airplanes with Mod. 40161	53-3023	0 or higher	Prior to 10000 total flight cycles
32	98-099-066(B)	42969 AND 45580	FUEL DENSITOMETERS - ATA 28	ALL Model A330 Airplanes	28-3044R1 OR 28-3053 and 28-3044R0	3044:1 or higher 3053: 0 or higher	Prior to 6 Years since new
33	98-101-068(B)	43306	MODIFY DOOR STOP FITTING ON PASS DOORS	ALL Model A330 Airplanes	53-3044	1 or higher	Prior to 10000 total flight cycles
34	98-268- 073(B)R1	45534	REPLACE MLG DOOR	All Airplanes with MLG door S/N AA1001 to AA1196; or SPAA001 to SPAA015	52-3049	0 or higher	Prior to 2/18/00 or C of A Issuance; whichever occurs later
35	98-291-074(B)	44030, OR 43761	REINFORCE FRAME 65 REAR FUSELAGE	ALL Model A330- 300 Airplanes	53-3058	2 or higher	Prior to 10000 total flight cycles
36	98-352-076(B)	46416	MOD MLG O/B PIN / BRAKE ROD TO MAIN STRUT	ALL Model A330 Airplanes	32-3084	2 or higher	Prior to 1/19/99 or C of A Issuance; whichever occurs later
37	98-454-082(B)	[43577]; OR [41652 AND 44440]; OR [41652 AND 44360]	LOWER KEELBEAM FITTING/FWD LOWER SHELL	ALL Model A330 Airplanes	57-3032	3 or higher	Prior to 6600 Total flight cycles or 21800 Total Flight Hrs, whichever occurs first

A330 Required Modification List (RML)

RML #	DGAC CN #	Mod #	Mandatory Action	Applicable To:	S/B #	S/B REV(s)	Compliance Time
38A	98-484-081(B)R1	46472	REPLACE PIVOT PINS OF SLIDE LOCKING MECHANISM	All Airplanes with 44860 (Type 1 Emerg Exits)	52-3050	1 or higher	Prior to 3/12/00 or C of A Issuance; whichever occurs later
38B	98-484-081(B)R1	46471	REPLACE PIVOT PINS OF SLIDE LOCKING MECHANISM	All Airplanes with 44330 (Mid & Aft Pax Doors)	52-3050	1 or higher	Prior to 3/12/00 or C of A Issuance; whichever occurs later
38C	98-484-081(B)R1	46473	REPLACE PIVOT PINS OF SLIDE LOCKING MECHANISM	All Airplanes with 44332 (Type A Emerg Exits)	52-3050	1 or higher	Prior to 3/12/00 or C of A Issuance; whichever occurs later
39	98-507-085(B)	[45090], OR [45155], OR [45197], OR [45904], OR [45904 and 45905]	REPLACE-DIAPHRAGM FOR EMERGENCY ACTUATOR	ALL Model A330 Airplanes	52-3048	1 or higher	Prior to 12/16/01 or C of A Issuance; whichever occurs later
40A	98-538-087(B)R1	46353	MODIFY DOOR STAY MECHANISM EMERG EXITS	All Airplanes with 44332 (Type A Emerg Exits)	52-3051	1 or higher	Prior to 3/31/00 or C of A Issuance; whichever occurs later
40B	98-538-087(B)R1	46352	MODIFY DOOR STAY MECHANISM MID/AFT EXITS	All Airplanes with 44330 (Mid & Aft Pax Doors)	52-3051	1 or higher	Prior to 3/31/00 or C of A Issuance; whichever occurs later

Hydraulic Fluids:

Type IV - Specification NSA 30.7110

Auxiliary Power Unit (APU):

Garrett Airesearch	GTCP 331-350C (Specification 31-7677A)
Maximum Allowable Speed	(107%) 41,730 RPM
Maximum Gas Temperature: Turbine Outlet Temperature Starting	650 °C 1250 °C

Approved oils: See Garrett report GT-7800 or Garrett Maintenance Manual.

Tires:

Refer to Airbus Industrie Service Bulletin (SB) A330-32-3004.

Service and Operating Information:

- Service and repair instructions (bulletins, letters, etc...), the structural repair manual, aircraft flight manual, and overhaul and maintenance manuals which contain a statement that the document is DGAC approved are accepted by the FAA and are considered as FAA approved. These approvals pertain to the type design only.
- Service Bulletins which have been approved under the authority of DGAC Design Organization Approval No. C01 (or, since Nov. 1996, approved under the authority of JAA Design Organization Approval No. F.JA.02), constitute DGAC approval and, therefore, FAA approval. The changes specified in the Service Bulletin have been approved by the DGAC when they are major, or under the authority of DGAC Design Organization Approval No.C01/F.JA.02 when they are minor. These approvals pertain to the type design only.

- Airplane operation must be in accordance with the DGAC-Approved Airplane Flight Manual (AFM), US version, listed below, applicable to the specific airplane model and serial number.

Model A330 Aircraft	Airbus Industrie Document Refr.	Revision No.	Date
-202	AI/ST-F 33000	2	January 6, 1999
-223	AI/ST-F 33000	2	January 6, 1999
-301	AI/EV-O 33000	3	January 6, 1999
-321, -322	AI/ST-F 33000	2	January 6, 1999
-323	AI/ST-F 33000	1	October 5, 1999

- Weight & Balance Manual - Refer to Airbus Industrie Documents 00G080A0006/C2S for A330-200 series aircraft and 00G080A0006/C3S for A330-300 series aircraft. See Note 1 for information on Weight and Balance.

See Note 3 for reference to the Instructions for Continued Airworthiness required under § 21.50 for service life limits on components, required inspections and inspection intervals, and certification maintenance requirements.

Notes:

- Note 1:** A current Weight and Balance report including list of the equipment included in the certificated empty weight, and loading instructions, when necessary, must be provided for each aircraft at the time of original airworthiness certification and at all times thereafter.
- Note 2:** Airplane operation must be in accordance with the applicable FAA approved Airplane Flight Manual. All placards required by either the FAA approved AFM, the applicable operating rules, or the certification basis must be installed in the airplane.
- Note 3:** Instructions For Continued Airworthiness:
- Component Life Limitations are provided in chapter 05, "Time Limits and Maintenance Checks", of the A330 Aircraft Maintenance Manual (AMM), approved by the DGAC. In addition, modification 47487, "Introduce Scallop on Growth Main Fitting to Improve Fatigue Life," is life-limited to 3000 Flight Cycles. It is expected that the mod 47487 life-limit will be extended on the basis of further fatigue tests and incorporated into a later revision of chapter 05.
 - Maintenance tasks to comply with Certification Maintenance Requirements (CMR's) for systems are listed in the A330 Certification Maintenance Requirements, Airbus Industrie Document 955.2074/93, Issue 12, dated October 1999, which is included as Appendix 1a of the Maintenance Review Board (MRB) report. The MRB report, issue date March 1998, is approved by the FAA (refr. Airbus Industrie Document 00G050A0002/C01).
 - Fatigue related structural inspections to comply with the damage tolerance requirements of the type certification are listed in the A330 Airworthiness Limitation Items, Airbus Industrie Document SE-M4/95A.0089/97, Issue 6, dated September 1999, which is included as Appendix 1b of the MRB report. The MRB report, issue date March 1998, is approved by the FAA (refr. Airbus Industrie Document 00G050A0002/C01).
- Note: Compliance with the FAA Required Modification List for Airbus Model A330 Aircraft as included under the Import Requirements section of TCDS Revision 4, dated March 21, 2000 or later TCDS revision, is necessary for an A330 aircraft to be found in a condition for safe operation.
- Note 4:** A330-301: If modification 42792, "Autoflight-FMGEC-Introduce L5 Standard on A330 Aircraft," is embodied the aircraft is qualified for CAT III precision approach and autoland. This does not constitute operational approval.
- Note 5:** A330-321 and A330-322: If modification 43397, "Autoflight-FMGEC-Certify CAT III Autoland for A330 with P&W engines," is embodied, the aircraft is qualified for CAT III precision approach and autoland. This does not constitute an operational approval.
- Note 6:** A330-202, A330-223 and A330-323: The aircraft Type Design is qualified for CAT III precision approach and autoland. This does not constitute an operational approval.
- Note 7:** ETOPS for the A330-323: The Type Design reliability and performance of this airframe-engine combination has been evaluated in accordance with AC 120-42A and found suitable for (180 minute maximum diversion time) Extended Range Operations with the incorporation of the approved airplane configuration CMP document (AI/EA5001, Revision 01, dated October 21, 1999). This finding does not constitute approval to conduct extended range operations.

...END...