

**MODELS:** Kaiser Fleetwings F-401, 4 PCAMM

**T.C. NUMBER:** 2-540

Engine	Jacobs L-5 or L-5MB (See Item 302)
Placard limits	Maximum, except takeoff - in. Hg., 2000 rpm (285 hp) Takeoff (one minute) - in. Hg., 2000 rpm (285 hp)
Placard speeds	Level flight or climb - 146 mph True Ind. Glide or dive - 214 mph True Ind. Flaps extended - 104 mph True Ind.
Fuel	52 gallons (two tanks at 26 gallons in wing) (+29)
Oil	5 gallons (+3)
No. passengers	3 (one -5, two +36)
Baggage	100 lbs. (+66)
Standard weight	3430 lbs.
C.G. limits	(+17) and (+23)
Spec. basis	Aero. Bulletin 7A, Section 3
Serial Nos.	1 only eligible

**EQUIPMENT:**

(Datum is wing leading edge)

**Class I:**

101.	Engine ring cowl	25 lbs.	
102.	Starter (Eclipse E-80)	22 lbs.	(-13)
103.	Generator - 15 amp	20 lbs.	(-8)
104.	Battery (Reading 6ARL)	28 lbs.	(+18)
105.	Landing lights (Grimes ST-250)	7 lbs.	(+17)
106.	Pressure fire extinguisher	19 lbs.	(-43)
107.	24 in. streamline wheels (Bendix) (Drawing No. 52736)		(+3)
108.	10x5 in. streamline tail wheel	5 lbs.	(+126)
109.	Propeller - fixed metal (Curtiss 55501)	54 lbs.	

**Class II:**

200. Miscellaneous items as noted in approved weight and balance report.

**Class III:**

301.	Anchor and rope	19 lbs.	(-65)
302.	Modified engine mount (required for L-5MB engine)		

**NOTE 1.** Eligible for export as follows subject to inspection for equipment specified in Chapter XII of Inspection Handbook (10/8/37):

- (a) Canada
  - Amphibian
  - Skiplane - not eligible. However, structure complies with Canadian requirements for ski installation.
- (b) All other countries except Great Britain and Australia.