

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

2A10
Revision 26
LAVIA S.A.

PA-25
PA-25-235
PA-25-260

March 25, 2008

TYPE CERTIFICATE DATA SHEET 2A10

This data sheet which is a part of Type Certificate No. 2A10 prescribes conditions and limitations under which the product for which the Type Certificate was issued meets the airworthiness requirements of the Civil Air Regulations and Federal Aviation Regulations.

Type Certificate Holder LAVIA ARGENTINA S.A. (LAVIASA)
Avenida Colón 412, P.B. Dpto B
C.P. 5500, Mendoza
Republica Argentina

Type Certificate Record of Name Change LATINOAMERICANA DE AVIACION (LAVIA S.A.) changed its trade name to LAVIA ARGENTINA S.A. (LAVIASA) on February 29, 2008 (TC reissued March 25, 2008)

I. Model PA-25, 1 PCLM (Restricted Category Only), Approved May 20, 1959.

Engine Lycoming O-320, O-320-A1A, O-320-A2A with carburetor setting 10-3678-11 or Lycoming O-320-A2B with carburetor setting 10-3678-32

Fuel 80/87 minimum grade aviation gasoline

Engine limits For all operations, 2700 r.p.m. (150 hp)

Propeller and Propeller limits McCauley 1A170-GM or Sensenich M74DM
Static r.p.m. at maximum permissible throttle setting:
Not over 2575 r.p.m., not under 2475 r.p.m.
No additional tolerance permitted.
Diameter: Not over 74 inches, not under 72.5 inches
Spinner required: Piper Drawing No. 14422

<u>Airspeed Limits (CAS)</u>	V _{ne} Never exceed 136 mph (118 knots)
	V _{no} Maximum structural cruising 108 mph (94 knots)
	V _p Maneuvering 107.5 mph (93 knots)
	V _{fe} Flaps Extended 95 mph (83 knots)

Center of Gravity Range (+11.7) to (+16.5) at 2300 lb.
(+10.0) to (+16.5) at 1600 lb. or less
Straight line variation between points given.

Empty Weight Center of Gravity Range None

Datum Leading edge of wing

Leveling Means Top longerons in cockpit bay

Page No.	1	2	3	4	5	6	7	8	9	10				
Rev. No.	26	25	25	25	24	25	24	24	24	24				

<u>Maximum Weight</u>	2300 lb.		
<u>No. of Seats</u>	1 at (+59)		
<u>Maximum Cargo</u>	800 lb. at (+14)		
<u>Fuel Capacity</u>	40 gallons at (-14.9) (one fuselage tank) See NOTE 1 for data on system fuel.		
<u>Oil Capacity</u>	8 quarts at (-47) (6 quarts usable) See NOTE 1 for data on system oil.		
<u>Control Surface Movements</u>	Wing Flaps		Down 57°
	Aileron	Up 23°	Down 23°
	Elevator	Up 28°	Down 15°
	Rudder	Right 25°	Left 25°
<u>Manufacturer's Serial Numbers</u>	25-1 through 25-731		

II. - Model PA-25-235, 1 PCLM (Restricted Category Only), Approved March 14, 1962.

<u>Engine</u>	Lycoming O-540-B2B5 or O-540-B2C5 with carburetor setting #10-4404-1		
<u>Fuel</u>	100/100LL Octane minimum grade aviation gasoline		
<u>Engine limits</u>	For all operations, 2575 r.p.m. (235 hp)		
<u>Propeller and Propeller Limits</u>	<ol style="list-style-type: none"> McCauley 1A200-FA (Eligible on Aircraft S/N 25-02; 25-2000 through 25-5521; and 25-7305522 through 25-8156024 produced by Piper Aircraft; LA-235-99501 and up produced by LAVIA S.A.): <ul style="list-style-type: none"> Static r.p.m. at maximum permissible throttle setting: <ul style="list-style-type: none"> Not over 2350 r.p.m., not under 2250 r.p.m. No additional tolerance permitted Diameter: Not over 84 inches, not under 82.3 inches Spinner required: Piper Drawing No. 64336 McCauley 1P235-AFA (Eligible on S/N 25-02, and 25-2000 through 25-4171): <ul style="list-style-type: none"> Static r.p.m. at maximum permissible throttle setting: <ul style="list-style-type: none"> Not over 2500 r.p.m., not under 2400 r.p.m. No additional tolerance permitted Diameter: Not over 84 inches, not under 82.3 inches Spinner required: Piper Drawing No. 14422 <p>See NOTE 6 for aircraft climb performance related to each propeller.</p>		
<u>Airspeed Limits</u> <u>(CAS)</u>	V_{ne}	Never exceed	156 mph (135 knots)
	V_{no}	Maximum structural cruising	124 mph (108 knots)
	V_p	Maneuvering	120 mph (104 knots)
	V_{fe}	Flaps Extended	109 mph (95 knots)
<u>Center of Gravity Range</u>	(+88.4) to (+92.5) at 2900 lb. (+85.6) to (+92.5) at 1793 lb. or less Straight line variation between points given.		
<u>Empty Weight</u> <u>Center of Gravity Range</u>	None		
<u>Datum</u>	78 inches forward of leading edge of wing		
<u>Leveling Means</u>	Top longerons in cockpit bay		

<u>Airspeed Limits</u> (CAS)	V_{ne}	Never exceed	156 mph	(135 knots)
	V_{no}	Maximum structural cruising	124 mph	(108 knots)
	V_p	Maneuvering	120 mph	(104 knots)
	V_{fe}	Flaps Extended	109 mph	(95 knots)
<u>Center of Gravity Range</u>	(+88.4)	to (+92.5)	at 2900 lb.	
	(+85.6)	to (+92.5)	at 1793 lb. or less	
	Straight line variation between points given.			
<u>Empty Weight</u>				
<u>Center of Gravity Range</u>	None			
<u>Datum</u>	78 inches forward of leading edge of wing			
<u>Leveling Means</u>	Top longerons in cockpit bay			
<u>Maximum Weight</u>	2900 lb.			
<u>No. of Seats</u>	1 at	(+135)		
<u>Maximum Cargo</u>	1200 lb. at	(+93)		
<u>Fuel Capacity</u>	S/N 25-4415 through 25-5521, and 25-7305522 through 25-7405572, and LA-260-98001, and subsequent produced by LAVIA S.A.:			
	38 gallons at (+63) (one wing tank)			
	S/N 25-7405573 through 25-8156024:			
	36 gallons at (+102) (two fuselage tanks)			
	For those Serial Numbers with modification applied to fuel tank (P/N 66058-01) under Service Letter No. 12:			
	200.6 liters (53 gallons)			
	S/N 25-4415 through 25-5521 and 25-7305522 through 25-7405572 produced by Piper Aircraft; and LA-260-98001 through LA-26099003 and LA-260-99005 through LA-260-06008 produced by LAVIA S.A.			
	See NOTE 1 for data on system fuel.			
<u>Oil Capacity</u>	12 quarts at	(+30) (9¼ quarts usable)		
	See NOTE 1 for data on system oil.			
<u>Control Surface Movements</u>	Wing Flaps		Down	57°
	Aileron	Up 23°	Down	23°
	Elevator	Up 28°	Down	15°
	Rudder	Right 25°	Left	25°
<u>Manufacturer's Serial Numbers</u>	25-4415 through 25-5521, and 25-7305522 through 25-8156024 produced by or under license of Piper Aircraft Corporation; LA-260-98001, and subsequent produced by LAVIA S.A.			
	See NOTE 7 for airworthiness certification eligibility in the United States.			

DATA PERTINENT TO ALL MODELS

<u>Certification Basis</u>	CAR 8.10(b), effective October 11, 1950. Restricted Type Certificate No. 2A10 issued May 20, 1959, for the special purpose of agricultural operations. Date of Application for Type Certificate March 7, 1959.
----------------------------	--

Production Basis

For aircraft models PA-25-235 S/N LA-235-99501 and up, and PA-25-260, S/N LA-260-98001, LA-260-99002, LA-260-99003, LA-260-99005 and up, production under type certificate only.

Equipment

The basic required equipment prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed on the aircraft for certification. In addition, the following items of equipment are required:

1.
 - a. FAA Approved Airplane Flight Manual dated May 20, 1959, for S/N 25-1 and 25-2 only.
 - b. FAA approved Flight manual Report 1024 dated October 20, 1999 for Models PA-25, S/N 25-1 through 25-731.
 - c. FAA approved flight Manual Report 1381 for Model PA-25-235. For Models PA-25-02 and 25-2000 and subsequent (Normal Category) and Subsequent.
 - Plus Weight and Balance Report No.1236 for S/N 25-02 (Restricted Category).
 - Plus Weight and Balance Report No. 1238 for S/N 25-2000 and subsequent (Restricted category).
 - d. FAA approved Flight Manual Report 1493 for Model PA-25-260- for S/N 25-4415 through 25-7405572 (Normal category)
 - plus Weight and Balance Report No. 1491 for S/ N 25-4415 through 25-7405572 (Restricted category).
 - e. FAA approved Flight Manual Report 1870 for Model 25-235, S/N 25-74005573 and subsequent (Normal category).
 - Plus Weight and Balance Report No. 1876 for S/N 25-7405579 and subsequent (Restricted category).
 - f. FAA approved Flight Manual Report 1871 for Model 25-260 S/N 25-7405573 and subsequent (Normal category).
 - g. FAA approved Flight Manual Report 1877 for Model 25-260 S/N 25-7405573 and subsequent (Restricted category).
 - h. DNA-approved Flight Manual Doc. No. LA-MV-235 for Model PA 25-235, S/N LA-235-99501 and subsequent (Restricted Category).
 - i. DNA-approved Flight Manual Doc. No. LA-MV-260 for Model PA 25-260, S/N LA-260-99001 and subsequent.
2. Sprayer and/or duster equipment installation in accordance with Piper Instructions Section XVI, Report VB-1 (Piper Report 1019), on S/N 25-3 through 25-1999.

Low volume installation:	52.5 lb. at	(+34.7)
High volume installation:	58.0 lb. at	(+37.7)
Duster installation:	32.0 lb. at	(+20.9)
3. Stall warning indicator device in accordance with Piper Drawing Nos. 61093 and 61128 on S/N 25-3 through 25-1999.

Piper Drawing Nos. 64031 and 64253 on S/N 25-02, 25-2000 through 25-4171; Piper Drawing Nos. 64031 and 64884 on S/N 25-4172 through 25-5521, and 25-7305522 through 25-8156024, LA-235-99501 and up, LA-260-98001 and subsequent.
4. Hopper installation per Piper Drawing No. 64211 and either sprayer installation per Piper Drawing No. 64152, or duster installation per Piper Drawing No. 64303 for S/N 25-02, 25-2000 through 25-2985.
5. Hopper installation per Piper Drawing No. 64511 and either sprayer installation per Piper Drawing No. 64586, or Duster installation per Piper Drawing No. 64599 for S/N 25-2986 through 25-5521, and 25-7305522 through 25-8156024, LA-235-99501 and up, LA-260-98001 and subsequent.

6. Installation of hopper with higher loading volume capacity of solid elements without
Incrementing the maximum permissible product loading weight (P/N 96116) under Service Letter no. 13.

<u>Affected Models</u>	<u>Affected Serial Numbers</u>
PA-25-235	25-3875 and up LA-235-XX501 and up
PA-25-260	25-3875 and up LA-260-99001 and up

See Note 9 for Optional Equipment Data

NOTE 1

Current weight and balance report including list of equipment included in certificated empty weight and loading instructions when necessary, must be provided for each aircraft at time of original certification.

The certificated empty weight and the corresponding center of gravity locations must include undrainable system oil (not included in oil capacity) and unusable fuel as noted below:

Model PA-25:	Fuel	14 lb.	at	(-23)
	Oil	3.2 lb.	at	(-47)
Model PA-25-235, S/N 25-02, 25-2000 through 25-3384:	Fuel	18 lb.	at	(+55)
	Oil	5.2 lb.	at	(+30)
Model PA-25-235, S/N 25-3385 through 25-5521, and 25-7305522 through 25-7405572, LA-235-99501 and up:	Fuel	12 lb.	at	(+55)
	Oil	5.2 lb.	at	(+30)
Model PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-7405572 LA-260-98001 and subsequent	Fuel	12lb	at	(+55)
	Oil	5.2 lb.	at	(+30)
Models PA-25-235 and PA-25-260, S/N 25-7405573 through 25-8156024:	Fuel	15 lb.	at	(+110)
	Oil	5.2 lb.	at	(+30)

NOTE 2

The following placards must be displayed:

- (a) In front and in clear view of the pilot:
- (1) On Model PA-25, S/N 25-1 through 25-1999:
"THIS AIRPLANE MUST BE OPERATED IN THE NORMAL CATEGORY IN COMPLIANCE WITH THE OPERATING LIMITATIONS STATED IN THE FORM OF PLACARDS, MARKINGS, AND MANUAL. ACROBATIC MANEUVERS (INCLUDING SPINS) PROHIBITED. FOR RESTRICTED CATEGORY OPERATION, REFER TO ADDITIONAL LIMITATIONS."
 - (2) On Model PA-25-235, S/N 25-02, 25-2000 through 25-2761:
"THIS AIRPLANE MUST BE OPERATED IN THE RESTRICTED CATEGORY IN COMPLIANCE WITH OPERATING LIMITATIONS STATED IN THE FORM OF PLACARDS AND MARKINGS. ACROBATIC MANEUVERS (INCLUDING SPINS) PROHIBITED."

- (3) On Model PA-25-235, S/N 25-2762 through 25-4414; and on Models PA-25-235 and PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-8156024:
"THIS AIRPLANE MUST BE OPERATED IN THE RESTRICTED CATEGORY IN COMPLIANCE WITH OPERATING LIMITATIONS STATED IN THE FORM OF PLACARDS AND MARKINGS. ACROBATIC MANEUVERS (INCLUDING SPINS) PROHIBITED. FOR NORMAL CATEGORY OPERATION, REFER TO FLIGHT MANUAL."
- (4) On Model PA-25-235, S/N LA-235-99501 and subsequent and Model PA-25-260, S/N LA-260-98001 and subsequent:
"THIS AIRPLANE MUST BE OPERATED IN THE RESTRICTED CATEGORY IN COMPLIANCE WITH THE OPERATING LIMITATIONS STATED IN THE FORM OF PLACARDS AND MARKINGS. ACROBATIC MANEUVERS (INCLUDING SPINS) PROHIBITED"
- (b) In cabin accessible to pilot for all Restricted Category PA-25, PA-25-235 and PA-25-260, display:
- "OPERATING LIMITATIONS - RESTRICTED CATEGORY ONLY."
THIS AIRPLANE HAS BEEN CERTIFIED IN COMPLIANCE WITH CAR 8 SPECIFICATIONS FOR THE SPECIAL PURPOSE OF AGRICULTURAL OPERATION AND PEST CONTROL. SPRAY AND DUST DISPENSING OPERATIONS ARE AUTHORIZED UNDER THE FOLLOWING LIMITATIONS:
1. THIS AIRPLANE SHOULD NOT BE OPERATED IN A MANNER THAT MAY ENDANGER LIFE AND PUBLIC PROPERTY . THE OPERATOR MUST MAKE SURE THAT THE AIRPLANE DOES NOT EXCEED THE MAXIMUM WEIGHT LIMITS AND IS LOADED WITHIN THE CENTER OF GRAVITY RANGE BEFORE TAKEOFF TO ENSURE A SAFETY MARGIN IN THE PERFORMANCE OF THE EXISTING OPERATIONS CONDITIONS, TAKING INTO ACCOUNT THE ZONE, ALTITUDE, TEMPERATURE AND TAKE OFF GROUND. SEE PLACARDS FOR MAXIMUM CAPACITY OF HOPPER AND FUEL TANKS.
 2. MANEUVERS SHOULD BE LIMITED TO THOSE NORMALLY PERFORMED FOR THE SPECIAL PURPOSE OF AGRICULTURAL OPERATION.
 3. AGRICULTURAL AND PEST CONTROL OPERATIONS SHOULD NOT BE CARRIED OUT OVER DENSELY POPULATED AREAS, IN CONGESTED AIR ROUTES OR IN THE VICINITY OF BUSY AIRPORTS WHERE PASSENGER TRANSPORT OPERATIONS ARE BEING CARRIED OUT.
 4. NEITHER CARGO NOR PASSENGERS SHALL BE TRANSPORTED FOR COMPENSATION OR HIRE.
 5. NOT MORE THAN THE MINIMUM NEEDED CREW SHALL BE TRANSPORTED DURING AGRICULTURAL OPERATIONS.
 6. IF THE AIRPLANE IS TO BE OPERATED IN A DIFFERENT CONFIGURATION FROM THE ORIGINAL CERTIFICATED CONFIGURATION, A NEW CERTIFICATION SHALL BE REQUIRED IN ACCORDANCE WITH CAR 8 SPECIFICATIONS.
 7. SULPHUR SPRAYING IS PROHIBITED UNTIL THE AIRPLANE IS MODIFIED IN COMPLIANCE WITH CAM 8. SEE FIRE PREVENTION, SECTION 6.0-6.17.
- (c) On hopper: Model PA-25: "800 lb. maximum"
Model PA-25-235: "1200 lb. maximum"
Model PA-25-260: "1200 lb. maximum"
- (d) On Models PA-25-235 and PA-25-260 - On checklist above instrument panel:
- "WINDOWS CLOSED"

- (e) On the instrument panel in full view of the pilot:
Models PA-25-235, S/N 25-2762 through 25-4414; and LA-235-99501 and up, and PA-25-235 or PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-8156024; Models PA-25-260, S/N LA-260-98001, LA-260-99002, LA-260-99003, LA-260-99005 and up –

"ROUGH AIR OR MANEUVERING SPEED 120 M.P.H."

- (f) - On safety panel above instrument panel in full view of the pilot:

- (1) Model PA-25-235, S/N 25-02 , 25-2000 through 25-3384

"UNUSABLE FUEL 3 GALLONS. WHEN FUEL QUANTITY INDICATOR READS ZERO, FUEL REMAINING IN TANK CANNOT BE USED SAFELY IN FLIGHT."

- (2) Models PA-25-235 S/N 25-3385 through 25-4414 and LA-235-99501 and up; and PA-25-235 or PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-7405572; and Model PA-25-260, S/N LA-260-98001, LA-260-99002, LA-260-99003, LA-260-99005 and up:

"UNUSABLE FUEL 2 GALLONS. WHEN FUEL QUANTITY INDICATOR READS ZERO, FUEL REMAINING IN TANK CANNOT BE USED SAFELY IN FLIGHT."

- (3) Model PA-25-235 or PA-25-260, S/N 25-7405573 through 25-8156024:

"UNUSABLE FUEL 2.5 GALLONS. WHEN FUEL QUANTITY INDICATOR READS ZERO, FUEL REMAINING IN TANK CANNOT BE USED SAFELY IN FLIGHT."

- (g) On Models PA-25-235 and PA-25-260 - On instrument panel in clear view of the pilot:

"NO SMOKING"

- (h) On Models PA-25-235, S/N 25-2762 through 25-4414 and LA-235-99501 and up; and PA-25-235 or PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-8156024; and Model PA-25-260, S/N LA-260-98001 and up - In front and in clear view of the pilot:

"STALL WARNING SYSTEM INOPERATIVE WHEN MASTER SWITCH IS OFF."

- (i) On Models PA-25-235 and PA-25-260, S/N 25-7405573 through 25-8156024 - Above and near the fuel quantity gauge:

"FUEL CAPACITY 36 GALLONS"

- (j) On Models PA-25-235, S/N LA-235-99501 and subsequent and PA-25-260, S/N 25-260-98001 and subsequent - Above and near the fuel quantity gauge:

"FUEL CAPACITY 38 GALLONS (143 LTS)"

- (k) Above and near to the fuel quantity indicator, in Model PA-25-235 and PA-25-260 with modification applied to fuel tank (P/N 66058-01) under Service Letter No. 12:

"FUEL CAPACITY 53 GALLONS (200.6 LTS)"

- (l) On Model PA-25-235 and PA-25-260, S/N 25-7405573 through 25-8156024 - Adjacent to low fuel level light on auxiliary instrument panel:

"LOW FUEL WARNING"

NOTE 3

The Model PA-25, S/N 25-2 through 25-1999 (Restricted Category) is the same as the Normal Category PA-25 except for installation of spray or dust dispensing equipment. Conversion from sprayer or duster configuration may be accomplished using Piper Instructions Section XVI of Report 1019. When operating in the Normal Category, FAA Type Certificate Data Sheet No. 2A8 will apply.

NOTE 4

In addition to the operating limitations in this data sheet, area economic, passenger, and other appropriate operating limitations in accordance with CAR 8 shall be shown on placards or listing accessible to the pilot.

- NOTE 5 (a) Model PA-25-235, S/N 25-2000 through 25-2761 are eligible for Multiple Airworthiness Certification when all placards are revised to the configuration of S/N 25-2762 through 25-25-5521, and 25-7305522 through 25-8156024. Airplane Flight Manual listed under equipment Item 1(d) of Type Certificate Data Sheet No. 2A8 required.
- (b) Model PA-25-235, S/N 25-2762 through 25-2985 are eligible for Multiple Airworthiness Certification in the Restricted Category and Normal Category in accordance with CAR 8.21 and Conversion Instructions, Section XVI of Piper Report VB-7, Revision No. 2, dated October 5, 1964. When operating in the Restricted Category, Type Certificate Data Sheet No. 2A10 shall apply. When operating in the Normal Category, Type Certificate Data Sheet No. 2A8 shall apply.
- (c) Model PA-25-235, S/N 25-2986 through 25-4414; and LA-235-99501 and up and Model PA-25-235 or PA-25-260, S/N 25-4415 through 25-5521, and 25-7305522 through 25-8156024; and Model PA25-260, S/N LA-260-98001, LA-260-99002, LA-260-99003, LA-260-99005 and up, are eligible for Multiple Airworthiness Certification in the Restricted Category and Normal Category in accordance with CAR 8.21 and Conversion Instructions, Section III of Piper Report VB-42, Revision No. 6, dated February 22, 1967. When operating in the Restricted Category, Type Certificate Data Sheet No. 2A10 shall apply. When operating in the Normal Category, Type Certificate Data Sheet No. 2A8 shall apply.

NOTE 6 Airplane Climb Performance - Sea Level, Standard Day:

<u>Configuration</u>	<u>Weight</u>	<u>Propeller</u>	<u>Rate of Climb</u>
"Duster"	2900 lb.	1P235-AFA	500 f.p.m.
		1A200-FA	440 f.p.m.

NOTE 7 The following S/N are not eligible for Airworthiness Certification in the United States:

25-4894, 25-5027, 25-5030, 25-5033, 25-5057, 25-5066, 25-5069, 25-5072, 25-5075, 25-5097, 25-5100, 25-5102, 25-5106, 25-5269, 25-5271, 25-5273, 25-5275, 25-5284 through 25-5293, 25-5315, 25-5316, 25-5318, 25-5320, 25-5454, 25-5455, 25-5456, 25-5457, 25-7305528, 25-7305530, 25-7305532, 25-7405591, 25-7405596, 25-7405613, 25-7405620, 25-7405631, 25-7405642, 25-7405652, 25-7405658, 25-7405662, 25-7405672, 25-7405679, 25-7405686, 25-7405690, 25-7405692, 25-7405694, 25-7405696, 25-7405698, 25-7405701, 25-7405704, 25-7405705, 25-7405706, 25-7405708, 25-7405714, 25-7405716, 25-7556030, 25-7556035, 25-7556040, 25-7556045, 25-7556050, 25-7556052, 25-7556057, 25-7556062, 25-7556065, 25-7556067, 25-7556069, 25-7556071, 25-7556073, 25-7556075, 25-7556077, 25-7556080, 25-7556090, 25-7556095, 25-7556100, 25-7556105, 25-7556110, 25-7556115, 25-7556120, 25-7556125, 25-7556135, 25-7556140, 25-7556145, 25-7556150, 25-7556153, 25-7556159, 25-7556162, 25-7556166, 25-7556226, 25-7556227, 25-7556228, 25-7556229, 25-7556230, 25-7556231, 25-7556232, 25-7556233, 25-7656078, 25-7656091, 25-7756072 through 25-7756081, 25-7756087 through 25-7756095, 25-7856001 through 25-7856004, 25-7856006, 25-7856008, 25-7856010, 25-7856012, 25-7856016, 25-7856018, 25-7856020, 25-7856022, 25-7856032, 25-7856034, 25-7856036, 25-7856038, 25-7856043, 25-7856045, 25-7856047, 25-7856049, 25-7856055, 25-7856057, 25-7856063, 25-7856065, 25-7856066, 25-7856067, 25-7856069, 25-7856071, 25-7956004, 25-7956006, 25-7956009 through 25-7956012, 25-7956014, 25-7956016, 25-7956019, 25-7956020, 25-7956022, 25-7956025, 25-7956027, 25-7956029, 25-7956031, 25-7956033, 25-7956036, 25-7956038, 25-7956041, 25-7956042, 25-8056004, 25-8056005, 25-8056008, 25-8056009, 25-8056011, 25-8056013, 25-8056016, 25-8056018, 25-8056021, 25-8056022, 25-8056026, 25-8056028, 25-8056041, 25-8056043, 25-8056046, and 25-8056048.

NOTE 8: Import Requirements:

(a) A United States airworthiness certificate may be issued on the basis of Argentina Certificate of Airworthiness for Export signed by a representative of Dirección Nacional de Aeronavegabilidad containing the following statement:

“The aircraft conforms to its U. S. type design (Type Certificate No 2A10) and is in a condition for safe operation.”

(b) The U. S. airworthiness certification basis for aircraft type certificated under 14 CFR Part 21 section 21.29 and exported by the country of manufacture is section 21.183(c) or 21.185(c).

(c) The U. S. airworthiness certification basis for aircraft type certificated under 14 CFR Part 21 section 21.29 and exported from countries other than the country of manufacture (e.g., third part country) is section 21.183(d) or 21.185(b).

....END.....